

Specification Sheet

Part Number: 151-00765

HellermannTyton Connector Clips provide a single method to mount connectors to various surfaces in a variety of applications.

Highly engineered designs feature anti-rattle discs, anti-rotation oval fir trees and clamps for mounting on edges.



An assortment of Connector Clips is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.

Connector Clip with Oval Fir Tree, 0.6-6.35 mm Panel Thick., 9.0x17.0 mm Hole Dia, PA66HIRHSUV, Black, 1000/ctn

Article Number	151-00765
Type	CC09
Color	Black (BK)
Quantity Per	pack
Product Description	Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.
Short Description	Connector Clip with Oval Fir Tree, 0.6-6.35 mm Panel Thick., 9.0x17.0 mm Hole Dia, PA66HIRHSUV, Black, 1000/ctn

Global Part Name	CC09-PA66HIRHSUV-BK
------------------	---------------------

Length L (Imperial)	1.30
---------------------	------

Length L (Metric)	33.05
-------------------	-------

Fixation Method	Fir Tree for oval holes
-----------------	-------------------------

Width W (Imperial)	0.85
--------------------	------

Width W (Metric)	21.59
------------------	-------

Height H (Imperial)	0.76
---------------------	------

Height H (Metric)	19.4
-------------------	------

Panel Thickness Min (Imperial)	0.02
--------------------------------	------

Panel Thickness Max (Imperial)	0.25
--------------------------------	------

Panel Thickness Min (Metric)	0.6
------------------------------	-----

Panel Thickness Max (Metric)	6.4
------------------------------	-----

Mounting Hole Diameter D (Imperial)	0.35 x 0.67 "
-------------------------------------	---------------

Mounting Hole Diameter D (Metric)	9.0 x 17.0 mm
-----------------------------------	---------------

Mounting Hole Diameter D Min (Imperial)	0.35
---	------

Mounting Hole Diameter D Max (Imperial)	0.35
---	------

Mounting Hole Diameter D Max (Metric)	9.0
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Operating Temperature intermittant, 1000 hours	+320°F (+160°C)
Operating Temperature intermittant, 5000 hours	+257°F (+125°C)
Operating Temperature intermittant, 500 hours	+329°F (+165°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)