

Specification Sheet

Part Number: 151-00783



Clip includes an internal rib that spans the inside of the bracket to fit securely into the profile of the tubing to prevent lateral movement and slipping of the tubing.

Extended fir tree allows for a wide range of panel thicknesses.

Fir tree design provides low insertion forces and high extraction forces.

Side Convoluted Tubing Clip, Max Bundle Diameter .6", PA66HIRHS, Black, 5000/pkg

Article Number 151-00783

Type CTCFT6

Color Black (BK)

Quantity Per pack

Product Description Convoluted Tube Clips provide a quick and easy method for firmly securing corrugated covered cables and wires to a surface. Applications such as this can be found in a wide variety of industries such as the wire harness, automotive, trucking, and heavy equipment manufacturing industries.

Short Description Side Convoluted Tubing Clip, Max Bundle Diameter .6", PA66HIRHS, Black, 5000/pkg

Global Part Name CTCFT6-PA66HIRHS-BK

| | |
|--------------------------------|----------|
| Length L (Imperial) | 0.43 |
| Length L (Metric) | 11.0 |
| Fixation Method | Fir Tree |
| Variant | Clips |
| Width W (Imperial) | 0.43 |
| Width W (Metric) | 11.0 |
| Bundle Diameter Min (Imperial) | 0.43 |
| Bundle Diameter Min (Metric) | 11.0 |
| Bundle Diameter Max (Imperial) | 0.59 |
| Bundle Diameter Max (Metric) | 15.0 |
| Height H (Imperial) | 0.73 |
| Height H (Metric) | 18.5 |
| Nominal Diameter (Imperial) | 1.56 |
| Nominal Diameter (Metric) | 15.0 |
| Panel Thickness Min (Imperial) | 0.03 |
| Panel Thickness Max (Imperial) | 0.18 |

| | |
|---|--|
| Panel Thickness Min (Metric) | 0.7 |
| Panel Thickness Max (Metric) | 4.5 |
| Mounting Hole Diameter D (Imperial) | 0.25 - 0.26 " |
| Mounting Hole Diameter D (Metric) | 6.3 - 6.7 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.25 |
| Mounting Hole Diameter D Max (Imperial) | 0.26 |
| Mounting Hole Diameter D Max (Metric) | 6.7 |
| Material | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut | PA66HIRHS |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 5003 |

Package Quantity (Metric) 5000

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)