

Specification Sheet

Part Number: 151-00814

H-Mounts utilize existing frame rail bolts eliminating the need for additional fasteners.

When used with cable ties, the H-Mounts eliminate the need to carry multiple sizes of fixed bundle diameter clamps which reduces inventory and purchasing costs.

Top tie slot allows bundles to be positioned in up to three locations, to provide multiple use options.

Side tie slots are curved to minimize bundle abrasion and position the bundles adjacent to the bolt yet away from the frame.



H-Mount for 0.75" standard bolts and Huck-Spin bolts, PA66HIRHSUV, Black, 900/pkg

Article Number 151-00814

Type HM7

Color Black (BK)

Quantity Per pack

| | |
|--------------------------------|--|
| Product Description | HellermannTyton H-Mounts offer a secure bundling solution that utilizes existing frame rail bolts which reduces component costs and improves installation time. The H-mounts have three bundle mounting locations each accommodating ties up to 1/2" wide. H-Mounts fasten with three bolt sizes: 1/2", 5/8", and 3/4". The top tie slot allows the bundle to be positioned directly over the bolt. The two curved tie slots on the sides position the bundles adjacent to the bolt yet away from the frame. |
| Short Description | H-Mount for 0.75" standard bolts and Huck-Spin bolts, PA66HIRHSUV, Black, 900/pkg |
| Global Part Name | HM7-PA66HIRHSUV-BK |
| Length L (Imperial) | 1.97 |
| Length L (Metric) | 50.0 |
| Fixation Method | Stud Mount |
| Width W (Imperial) | 1.02 |
| Width W (Metric) | 25.98 |
| Height H (Imperial) | 1.10 |
| Height H (Metric) | 28.0 |
| Cable Tie Width Max (Imperial) | 0.052 |
| Cable Tie Width Max (Metric) | 13.2 |
| Bolt Size | 3/4 " |
| Stud Diameter (Metric) | 19.05 mm |

| | |
|------------------------------|--|
| Stud Diameter (Imperial) | 0.75 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL 94 HB |
| UV Resistant (Yes/No) | Yes |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 900 |
| Package Quantity (Metric) | 900 |
| Customs Number | 3926909988 |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Privacy Policy](#)

[Cookie Policy](#)

[Terms and Conditions](#)