

Specification Sheet

Part Number: 151-01243

HellermannTyton Connector Clips provide a single method to mount connectors to various surfaces in a variety of applications.

Highly engineered designs feature anti-rattle discs, anti-rotation oval fir trees and clamps for mounting on edges.



An assortment of Connector Clips is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.

Connector Clip with Round Arrowhead, 5.35mm Hole Dia, PA66HIRHS, Natural, 4000/carton

Article Number 151-01243

Type CC14

Color Natural (NA)

Quantity Per pack

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Connector Clip with Round Arrowhead, 5.35mm Hole Dia, PA66HIRHS, Natural, 4000/carton

Global Part Name CC14-PA66HIRHS-NA

Length L (Imperial)	1.00
Length L (Metric)	25.48
Fixation Method	Arrowhead
Variant	5.0 - 5.7 mm
Width W (Imperial)	0.68
Width W (Metric)	16.66
Height H (Imperial)	0.54
Height H (Metric)	13.6
Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.06
Panel Thickness Min (Metric)	0.65
Panel Thickness Max (Metric)	1.4
Mounting Hole Diameter D (Imperial)	0.2 - 0.22 "
Mounting Hole Diameter D (Metric)	5.0 - 5.7 mm
Mounting Hole Diameter D Min (Imperial)	0.2

Mounting Hole Diameter D Max (Imperial) 0.22

Mounting Hole Diameter D Max (Metric) 5.7

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

UV Resistant (Yes/No) No

Use Conditions For Indoor Use Only

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Operating Temperature intermittent, 1000 hours +320°F (+160°C)

Operating Temperature intermittent, 5000 hours +257°F (+125°C)

Operating Temperature intermittent, 500 hours +329°F (+165°C)

Reach Compliant (Article 33) Yes

Package Quantity (Imperial) 4000

Package Quantity (Metric) 4000

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)