

## Specification Sheet

Part Number: 151-01612

Easy to install, remove and reposition with just a quarter-turn – no tools necessary.

Multi-directional cable tie slot allows for routing a bundle parallel to or perpendicular to the frame.

Low profile is ideal for cramped spaces.

Designed to fit an 80/20 profile with a T-slot of 8 mm (0.32") and external dimensions of 40 mm (1.5").



Aluminum Frame Mount for 40mm or 1.5" Frame, 4.0 - 4.8mm Panel Thickness, PA66, White, 100/bg

Article Number 151-01612

Type AFLM40-1

Color Natural (NA)

Quantity Per pack

Product Description Aluminum frame mounts can be used with 20, 30 or 40 mm square frames from the major aluminum frame manufacturers. As there is no need to screw them in place, these mounts offer maximum ease of use and fast installation.

Short Description Aluminum Frame Mount for 40mm or 1.5" Frame, 4.0 - 4.8mm Panel Thickness, PA66, White, 100/bg

Global Part Name AFLM40-1-PA66-NA

Length L (Imperial) 1.10

Length L (Metric) 28.0

Fixation Method Profile rail

Width W (Imperial) 0.83

Width W (Metric) 21

Cable Ties T18 - T50

Height H (Imperial) 0.80

Height H (Metric) 20.2

Panel Thickness Min (Imperial) 0.16

Panel Thickness Max (Imperial) 0.19

Panel Thickness Min (Metric) 4.0

Panel Thickness Max (Metric) 4.8

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability	UL 94 V-2
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)