

## Specification Sheet

Part Number: 151-01629


For use with HellermannTyton T18 - T30 cable ties to provide stability when securing bundles.

4-way opening allows cable ties to be installed parallel or perpendicular to bundles.

The high-heat, high-bond adhesive is ideal for outdoor applications, with a static load weight of 0.6 lb.

Two predrilled holes extend mounting options and solutions.

Extended adhesive liner is easy to remove quickly.



High Heat High Bond Acrylic Adhesive Base, 0.75 x 0.75", Use T18-T30 Tie, PA66HIRHSUV, Black, 100/pkg

|                |           |
|----------------|-----------|
| Article Number | 151-01629 |
|----------------|-----------|

|      |       |
|------|-------|
| Type | MB3A4 |
|------|-------|

|       |            |
|-------|------------|
| Color | Black (BK) |
|-------|------------|

|              |      |
|--------------|------|
| Quantity Per | pack |
|--------------|------|

|                     |                                                                                                                                                                                                                                                                                 |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | MB3A4 adhesive mounts are for use with HellermannTyton T18 - T30 Series cable ties to provide stability when securing bundles. The high-heat, high-bond acrylic adhesive-backed mounts can be used to secure a bundle and have two predrilled holes to extend mounting options. |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                     |                                                                                                       |
|-------------------------------------|-------------------------------------------------------------------------------------------------------|
| Short Description                   | High Heat High Bond Acrylic Adhesive Base, 0.75 x 0.75", Use T18-T30 Tie, PA66HIRHSUV, Black, 100/pkg |
| Global Part Name                    | MB3A4-PA66HIRHSUV-BK                                                                                  |
| Length L (Imperial)                 | 0.75                                                                                                  |
| Length L (Metric)                   | 19.0                                                                                                  |
| Fixation Method                     | Adhesive                                                                                              |
| Width W (Imperial)                  | 0.75                                                                                                  |
| Width W (Metric)                    | 19.0                                                                                                  |
| Cable Ties                          | T18 - T30                                                                                             |
| Height H (Imperial)                 | .19                                                                                                   |
| Height H (Metric)                   | 4.8                                                                                                   |
| Cable Tie Width Max (Imperial)      | 0.14                                                                                                  |
| Cable Tie Width Max (Metric)        | 3.6                                                                                                   |
| Mounting Hole Diameter D (Imperial) | 0.12 "                                                                                                |
| Mounting Hole Diameter D (Metric)   | 3.0 mm                                                                                                |
| Mounting Hole Centers (Imperial)    | 0.52                                                                                                  |

|                                                |                                                                          |  |
|------------------------------------------------|--------------------------------------------------------------------------|--|
| Material                                       | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |  |
| Material Shortcut                              | PA66HIRHSUV                                                              |  |
| Adhesive                                       | Acrylic foam                                                             |  |
| Flammability                                   | UL 94 HB (excluding adhesive)                                            |  |
| UV Resistant (Yes/No)                          | Yes                                                                      |  |
| Use Conditions                                 | For Indoor and Outdoor Use                                               |  |
| Adhesive Operating Temperature                 | -40°F to +176°F (-40°C to +80°C)                                         |  |
| Operating Temperature                          | -40°F to +221°F (-40°C to +105°C)                                        |  |
| Operating Temperature intermittant, 1000 hours | +320°F (+160°C)                                                          |  |
| Operating Temperature intermittant, 5000 hours | +257°F (+125°C)                                                          |  |
| Operating Temperature intermittant, 500 hours  | +329°F (+165°C)                                                          |  |
| Reach Compliant (Article 33)                   | Yes                                                                      |  |
| ROHS Compliant                                 | Yes                                                                      |  |
| Package Quantity (Imperial)                    | 100                                                                      |  |
| Package Quantity (Metric)                      | 100                                                                      |  |

Customs Number

3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Privacy Policy](#)   [Cookie Policy](#)   [Terms and Conditions](#)