

Specification Sheet

Part Number: 151-01769



Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.

Controlled flex and angled entry promote easy installation.

Non-rotating fir tree demonstrates easy insertion with high extraction resistance.

MOC Clip, 14 mm, with 4 x Oval Fir Tree, PA66HIRHSUV, Black, 3000/ctn

Article Number 151-01769

Type MOC14FTOVAL

Color Black (BK)

Quantity Per pack

Product Description The MOC with Oval Fir Tree features HellermannTyton's unique retention clip attached to a 4x oval fir tree that will not rotate in the mounting hole. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point against a panel. This one design exceeds automotive requirements for the four most common oval sizes: 6.2x12.2 mm, 6.5x12.5 mm, 6.5x13 mm and 7x12 mm.

Short Description MOC Clip, 14 mm, with 4 x Oval Fir Tree, PA66HIRHSUV, Black, 3000/ctn

Global Part Name MOC14FTOVAL-PA66HIRHSUV-BK

Length L (Imperial) 0.93

Length L (Metric) 23.6

Fixation Method Fir Tree

Bundle Diameter Min (Imperial) 0.53

Bundle Diameter Min (Metric) 13.5

Bundle Diameter Max (Imperial) 0.62

Bundle Diameter Max (Metric) 15.8

Height H (Imperial) 1.61

Height H (Metric) 40.9

Depth D (Imperial) 0.39

Depth D (Metric) 10.0

Panel Thickness Min (Imperial) 0.02

Panel Thickness Max (Imperial) 0.27

Panel Thickness Min (Metric) 0.6

Panel Thickness Max (Metric) 6.75

Mounting Hole Diameter D (Imperial) 0.26 x 0.51 " 0.27" x 0.47 " 0.24 x 0.48 " 0.28 x 0.47 " 0.26 x 0.49 "

Mounting Hole Diameter D (Metric) 6.5 x 13.0 mm 7.0 x 12.0 mm 6.5 x 12.5 mm 6.2 x 12.2 mm

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

Halogen Free Yes

UV Resistant (Yes/No) Yes

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Operating Temperature intermittent, 1000 hours +320°F (+160°C)

Operating Temperature intermittent, 5000 hours +257°F (+125°C)

Operating Temperature intermittent, 500 hours +329°F (+165°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)