

## Specification Sheet

Part Number: 151-02432

The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters.

Clip can be installed by hand – no need for hardware or tools.

Design provides low insertion and high extraction force, for simple, secure performance.



Clip keeps bundle away from areas that could cause damage due to rubbing.

Standoff Bundling Clip, 2.4" Long, 0.03 - 0.22" Panel Thickness, PA66HIRHS, Natural, 2500/carton

Article Number 151-02432

Type SOC8FT8

Color Natural (NA)

Quantity Per pack

Product Description Tape clips are designed to provide simple and easy methods of securing cable bundles, hoses, or pipes.

Short Description Standoff Bundling Clip, 2.4" Long, 0.03 - 0.22" Panel Thickness, PA66HIRHS, Natural, 2500/carton

Global Part Name SOC8FT8-PA66HIRHS-NA

Length L (Imperial)	2.4
Length L (Metric)	61
Offset Length (Imperial)	0.625
Offset Length (Metric)	15.9
Fixation Method	Fir Tree
Width W (Imperial)	0.47
Width W (Metric)	12.0
Height H (Imperial)	0.88
Height H (Metric)	22.4
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.22
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	5.5
Mounting Hole Diameter D (Imperial)	0.30 - 0.39 "
Mounting Hole Diameter D (Metric)	M10 x 1.5 7.6 - 10.0 mm
Mounting Hole Diameter D Min (Imperial)	0.29

Mounting Hole Diameter D Max (Imperial)	0.32
Mounting Hole Diameter D Max (Metric)	10.0
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Operating Temperature intermittant, 1000 hours	+320°F (+160°C)
Operating Temperature intermittant, 5000 hours	+257°F (+125°C)
Operating Temperature intermittant, 500 hours	+329°F (+165°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes

Package Quantity (Imperial)	2500
Package Quantity (Metric)	2500
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)