

## Specification Sheet

Part Number: 151-03103



Mount and tie combination makes it easy to service bundles in the field.

Eliminates the need for multiple sized diameter clamps.

Low fire hazard materials comply with stringent NFPA 130 safety standards and improve opportunities to get product specified at the engineering stage of a project.

High Torque Mount, 0.327" Mounting Hole Dia, 114.0 lb/ft Max Torque, PA666V0, Black, 500/pkg

Article Number 151-03103

Type HDM320

Color Black (BK)

Quantity Per pack

Product Description The saddle design minimizes pinching and crushing of wires and adjusts to a wide variety of bundle diameters when used with HellermannTyton heavy duty T120, T150 or Wide Strap Cable Ties. Metal bushing provides strength for high-torque applications. Low fire hazard material is designed specifically for rail applications.

Short Description High Torque Mount, 0.327" Mounting Hole Dia, 114.0 lb/ft Max Torque, PA666V0, Black, 500/pkg

Global Part Name	HDM320-PA666V0-BK
Length L (Imperial)	1.82
Length L (Metric)	46.5
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	0.98
Width W (Metric)	25.0
Height H (Imperial)	0.81
Height H (Metric)	20.7
Cable Tie Width Max (Imperial)	0.5
Cable Tie Width Max (Metric)	12.7
Mounting Hole Diameter D (Imperial)	0.33 "
Mounting Hole Diameter D (Metric)	8.31 mm
Stud Diameter (Metric)	8.0 mm
Stud Diameter (Imperial)	0.31
Material	Polyamide 6.6/6, V0 (PA666V0)

Material Shortcut	PA666V0
Flammability	UL 94 V-0
Halogen Free	Yes
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +248°F (-40°C to +120°C)
Maximum Torque (kgf-cm)	1576.11
Maximum Torque (lbf-ft)	114
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Certification/Specification	ASTM 1354 Exova   NFPA130: 2017 ASTM E 162 ASTM E 662
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Privacy Policy](#)

[Cookie Policy](#)

[Terms and Conditions](#)