

## Specification Sheet

Part Number: MB5A0C2

For use with HellermannTyton T18 - T150 cable ties to provide stability when securing bundles.

4-way opening allows cable ties to be installed parallel or perpendicular to bundles.

The rubber-based adhesive is an economical choice ideal for indoor applications, with a static load weight of 2.1 lb.

Two predrilled holes extend mounting options and solutions.

Extended adhesive liner is easy to remove quickly.



Rubber Adhesive Cable Tie Mount, 1.49 x 1.49", Use With T18-T150 Cable Tie, PA66, Black, 100/pkg

|                |           |
|----------------|-----------|
| Article Number | 151-28602 |
|----------------|-----------|

|      |      |
|------|------|
| Type | MB5A |
|------|------|

|       |            |
|-------|------------|
| Color | Black (BK) |
|-------|------------|

|              |      |
|--------------|------|
| Quantity Per | pack |
|--------------|------|

|                     |                                                                                                                                                                                                                                                           |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | MB5A adhesive mounts are for use with HellermannTyton T18 - T150 Series cable ties to provide stability when securing bundles. The rubber adhesive-backed mounts can be used to secure a bundle and have two predrilled holes to extend mounting options. |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                     |                                                                                                  |
|-------------------------------------|--------------------------------------------------------------------------------------------------|
| Short Description                   | Rubber Adhesive Cable Tie Mount, 1.49 x 1.49", Use With T18-T150 Cable Tie, PA66, Black, 100/pkg |
| Global Part Name                    | MB5A-PA66-BK                                                                                     |
| Length L (Imperial)                 | 1.49                                                                                             |
| Length L (Metric)                   | 37.7                                                                                             |
| Fixation Method                     | Adhesive                                                                                         |
| Width W (Imperial)                  | 1.49                                                                                             |
| Width W (Metric)                    | 37.7                                                                                             |
| Cable Ties                          | T18 - T150                                                                                       |
| Height H (Imperial)                 | 0.28                                                                                             |
| Height H (Metric)                   | 7.1                                                                                              |
| Cable Tie Width Max (Imperial)      | 0.35                                                                                             |
| Cable Tie Width Max (Metric)        | 8.9                                                                                              |
| Mounting Hole Diameter D (Imperial) | 0.19 "                                                                                           |
| Mounting Hole Diameter D (Metric)   | 4.8 mm                                                                                           |
| Mounting Hole Centers (Imperial)    | 1.0                                                                                              |

|                                |                                                 |
|--------------------------------|-------------------------------------------------|
| Material                       | Polyamide 6.6 (PA66)                            |
| Material Shortcut              | PA66                                            |
| Adhesive                       | Synthetic rubber with base of polyethylene foam |
| Flammability                   | UL 94 V-2 (excluding adhesive)                  |
| Halogen Free                   | Yes                                             |
| UV Resistant (Yes/No)          | No                                              |
| Use Conditions                 | For Indoor and Outdoor Use                      |
| Adhesive Operating Temperature | 0°F to +150°F (-18 °C to +66 °C)                |
| Operating Temperature          | -40°F to +185°F (-40°C to +85°C)                |
| BABA Compliant                 | YES                                             |
| Reach Compliant (Article 33)   | Yes                                             |
| ROHS Compliant                 | Yes                                             |
| Package Quantity (Imperial)    | 100                                             |
| Package Quantity (Metric)      | 100                                             |
| Customs Number                 | 3926909988                                      |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Privacy Policy](#)   [Cookie Policy](#)   [Terms and Conditions](#)