

Specification Sheet

Part Number: 156-00588



Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.

Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

2-Piece Cable Tie with Edge Clip, 8.0" Long, EC4B, 1 - 3 mm Panel, 50lb, PA66UV/PA66HIRHS, Black, 100/pkg

|                     |                                                                                                                                                                                                                                                                                                                                            |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 156-00588                                                                                                                                                                                                                                                                                                                                  |
| Type                | T50REC4B                                                                                                                                                                                                                                                                                                                                   |
| Color               | Black (BK)                                                                                                                                                                                                                                                                                                                                 |
| Quantity Per        | pack                                                                                                                                                                                                                                                                                                                                       |
| Product Description | HellermannTyton's Two Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place. |
| Short Description   | 2-Piece Cable Tie with Edge Clip, 8.0" Long, EC4B, 1 - 3 mm Panel, 50lb, PA66UV/PA66HIRHS, Black, 100/pkg                                                                                                                                                                                                                                  |
| Global Part Name    | T50REC4B-PA66UV/PA66HIRHS-BK                                                                                                                                                                                                                                                                                                               |

|                                     |                 |
|-------------------------------------|-----------------|
| Minimum Tensile Strength (Imperial) | 50              |
| Minimum Tensile Strength (Metric)   | 225             |
| Length L (Imperial)                 | 8.0             |
| Length L (Metric)                   | 202.0           |
| Fixation Method                     | Edge Clip       |
| Identification Plate Position       | none            |
| Releasable Closure                  | No              |
| Variant                             | Inside Serrated |
| Width W (Imperial)                  | 0.18            |
| Width W (Metric)                    | 4.6             |
| Bundle Diameter Min (Imperial)      | 0.16            |
| Bundle Diameter Min (Metric)        | 4.0             |
| Bundle Diameter Max (Imperial)      | 1.77            |
| Bundle Diameter Max (Metric)        | 45.0            |
| Thickness T (Imperial)              | 0.05            |
| Thickness T (Metric)                | 1.2             |

|                                |                                                                                                       |
|--------------------------------|-------------------------------------------------------------------------------------------------------|
| Height H (Imperial)            | 0.63                                                                                                  |
| Height H (Metric)              | 16.0                                                                                                  |
| Panel Thickness Min (Imperial) | 0.04                                                                                                  |
| Panel Thickness Max (Imperial) | 0.12                                                                                                  |
| Panel Thickness Min (Metric)   | 1.0                                                                                                   |
| Panel Thickness Max (Metric)   | 3.0                                                                                                   |
| Material                       | Polyamide 6.6 UV-stabilized (PA66UV) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Foot Part Material             | PA66HIRHSUV                                                                                           |
| Material Shortcut              | PA66UV PA66HIRHS                                                                                      |
| Material Cable Tie             | Polyamide 6.6 UV-stabilized (PA66UV)                                                                  |
| Flammability                   | UL 94 HB                                                                                              |
| UV Resistant (Yes/No)          | Yes                                                                                                   |
| Use Conditions                 | For Indoor and Outdoor Use                                                                            |
| Operating Temperature          | -40°F to +221°F (-40°C to +105°C) -40°F to +257°F (-40°C to +125°C)                                   |
| Reach Compliant (Article 33)   | Yes                                                                                                   |

|                             |            |
|-----------------------------|------------|
| ROHS Compliant              | Yes        |
| Package Quantity (Imperial) | 100        |
| Package Quantity (Metric)   | 100        |
| Customs Number              | 3926909988 |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Privacy Policy](#)   [Cookie Policy](#)   [Terms and Conditions](#)