

## Specification Sheet

Part Number: 156-01341



Bundle can rotate to any orientation, allowing routing in any direction regardless of mounting point.

2-piece design allows installer to slide clip around cable tie to obtain optimum orientation

Clip is reusable, making relocation or adjustments simple.

2-Piece Cable Tie with Pipe Clip, 6.0" Long, Attaches to Diameter 0.75 - 0.96", PA66HS/PA66HIRHS, Black, 500/pkg

Article Number 156-01341

Type T50SVCOC19-24.5

Color Black (BK)

Quantity Per pack

Product Description HellermannTyton's 2-Piece Cable Tie with Pipe Clip secures cables to tubular frame rails. The cable tie bundles wires, cables or tubes, and the C-clip snaps onto the tubular frame rail. The clip can be removed from the mounting surface and reinstalled without additional fasteners.

Short Description 2-Piece Cable Tie with Pipe Clip, 6.0" Long, Attaches to Diameter 0.75 - 0.96", PA66HS/PA66HIRHS, Black, 500/pkg

Global Part Name T50SVCOC19-24.5-PA66HS/PA66HIRHS-BK

|                                     |              |
|-------------------------------------|--------------|
| Minimum Tensile Strength (Imperial) | 50           |
| Minimum Tensile Strength (Metric)   | 222          |
| Length L (Imperial)                 | 6.1          |
| Length L (Metric)                   | 155.0        |
| Fixation Method                     | Omega Clip   |
| Identification Plate Position       | none         |
| Tie Closure                         | plastic pawl |
| Width W (Imperial)                  | 0.19         |
| Width W (Metric)                    | 4.7          |
| Bundle Diameter Min (Imperial)      | 0.08         |
| Bundle Diameter Min (Metric)        | 2.0          |
| Bundle Diameter Max (Imperial)      | 1.38         |
| Bundle Diameter Max (Metric)        | 35.0         |
| Thickness T (Imperial)              | 0.05         |
| Thickness T (Metric)                | 1.35         |

|                              |   |
|------------------------------|---|
| Material                     | Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Foot Part Material           | PA66HIRHS   |
| Material Shortcut            | PA66HS PA66HIRHS  |
| Material Cable Tie           | Polyamide 6.6 heat stabilized (PA66HS)  |
| Flammability                 | UL 94 HB  |
| UV Resistant (Yes/No)        | No  |
| Use Conditions               | For Indoor and Outdoor Use  |
| Operating Temperature        | -40°F to +221°F (-40°C to +105°C)   |
| Reach Compliant (Article 33) | Yes   |
| ROHS Compliant               | Yes   |
| Package Quantity (Imperial)  | 500   |
| Package Quantity (Metric)    | 500   |
| Customs Number               | 3926909988  |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.