

## Specification Sheet

Part Number: 156-01348

Bundle can rotate to any orientation, allowing routing in any direction regardless of mounting point.

2-piece design allows installer to slide clip around cable tie to obtain optimum orientation

Clip is reusable, making relocation or adjustments simple



2-Piece Cable Tie with Pipe Clip, 39-45mm, PA66HIRHS, Black, 250/pkg

Article Number 156-01348

Type T50SMVCOC39-45

Color Black (BK)

Quantity Per pack

Product Description HellermannTyton's 2-Piece Cable Tie with Pipe Clip secures cables to tubular frame rails. The cable tie bundles wires, cables or tubes, and the C-clip snaps onto the tubular frame rail. The clip can be removed from the mounting surface and reinstalled without additional fasteners.

Short Description 2-Piece Cable Tie with Pipe Clip, 39-45mm, PA66HIRHS, Black, 250/pkg

Global Part Name T50SMVCOC39-45-PA66HS/PA66HIRHS-BK

|                                     |   |
|-------------------------------------|---|
| Minimum Tensile Strength (Imperial) | 50  |
| Minimum Tensile Strength (Metric)   | 222   |
| Length L (Imperial)                 | 8.3   |
| Length L (Metric)                   | 210.0   |
| Fixation Method                     | Omega Clip  |
| Identification Plate Position       | none  |
| Width W (Imperial)                  | 0.19  |
| Width W (Metric)                    | 4.7   |
| Bundle Diameter Min (Imperial)      | 0.08  |
| Bundle Diameter Min (Metric)        | 2.0   |
| Bundle Diameter Max (Imperial)      | 1.97  |
| Bundle Diameter Max (Metric)        | 50.0  |
| Thickness T (Metric)                | 1.35  |
| Material                            | Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |

|                              |  |
|------------------------------|--|
| Foot Part Material           | PA66HIRHS                              |
| Material Shortcut            | PA66HIRHS PA66HS                       |
| Material Cable Tie           | Polyamide 6.6 heat stabilized (PA66HS) |
| Flammability                 | UL 94 HB                               |
| UV Resistant (Yes/No)        | No                                     |
| Use Conditions               | For Indoor and Outdoor Use             |
| Operating Temperature        | -40°F to +221°F (-40°C to +105°C)      |
| Reach Compliant (Article 33) | Yes                                    |
| ROHS Compliant               | Yes                                    |
| Package Quantity (Imperial)  | 250                                    |
| Package Quantity (Metric)    | 250                                    |
| Customs Number               | 3926909988                             |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)