

## Specification Sheet

Part Number: 156-01726

Delivers high pull-out force for reliable performance, yet it's easy to install.

Reusable fastener can be extracted from threaded or nonthreaded holes using a 5/16" hex driver.

Heat-stabilized material provides excellent resistance to high temperatures.



Blind Hole Mount Outside Serrated Cable Tie for 1/4" Thread/Non-Thread Hole, 8", 50lb, PA66HS, Black, 500/bg

Article Number 156-01726

Type T50RBHMB

Color Black (BK)

Quantity Per pack

**Product Description**  
HellermannTyton Blind Hole Mount Cable Ties for threaded and nonthreaded holes offer an easy-to-use method for bundling and affixing cables. The two-piece design includes a heat-stabilized cable tie and formula-matched, 1/4" mount that features a low push-in force and aggressively resists pull out. Performs equally well in threaded or nonthreaded blind holes. Mount can slide along cable tie to adjust orientation if needed. Fastener can be removed from hole using a hex driver, ensuring reuse if desired.

**Short Description**  
Blind Hole Mount Outside Serrated Cable Tie for 1/4" Thread/Non-Thread Hole, 8", 50lb, PA66HS, Black, 500/bg

Global Part Name T50RBHMB-PA66HS-BK

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 8.0

Length L (Metric) 203.2

Fixation Method Blind Plug

Identification Plate Position none

Width W (Imperial) 0.31

Width W (Metric) 7.8

Bundle Diameter Min (Imperial) 0.1

Bundle Diameter Min (Metric) 2.5

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 50.0

Height H (Imperial) 0.736

Height H (Metric) 18.7

Diameter D (Imperial) 0.25

|   |  |
|---|--|
| Diameter D (Metric)                     | 6.35                                   |
| Mounting Hole Diameter D (Imperial)     | 0.246 - 0.253 "                        |
| Mounting Hole Diameter D (Metric)       | 6.25 - 6.45 mm                         |
| Mounting Hole Diameter D Min (Imperial) | 0.25                                   |
| Mounting Hole Diameter D Max (Imperial) | 0.25                                   |
| Mounting Hole Diameter D Max (Metric)   | 6.45                                   |
| Disc Diameter (Metric)                  | 10.9                                   |
| Disc Diameter (Imperial)                | 0.43                                   |
| Material                                | Polyamide 6.6 heat stabilized (PA66HS) |
| Foot Part Material                      | PA66HS                                 |
| Material Shortcut                       | PA66HS                                 |
| Material Cable Tie                      | Polyamide 6.6 heat stabilized (PA66HS) |
| Flammability                            | UL 94 V-2                              |
| Halogen Free                            | No                                     |
| UV Resistant (Yes/No)                   | No                                     |

|                              |                                   |
|------------------------------|-----------------------------------|
| Use Conditions               | For Indoor and Outdoor Use        |
| Operating Temperature        | -40°F to +257°F (-40°C to +125°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Package Quantity (Imperial)  | 500                               |
| Package Quantity (Metric)    | 500                               |
| Customs Number               | 3926909988                        |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Privacy Policy](#)   [Cookie Policy](#)   [Terms and Conditions](#)