


Specification Sheet

Part Number: 156-02434

Versatile and robust fir tree design provides low insertion effort yet delivers exceptional retention strength in an 6.5 mm hole and M8 threaded hole.

Wider and thinner strap design increases flexibility and minimizes pinching of bundles, hoses and tubing.

PA46 nylon material provides great performance at up to 135°F continuous operating temperature.



2-Piece Cable Tie with Fir Tree Mount, 6.5mm Hole and M8 Threaded Hole, PA46, Brown, 1200/ctn

Article Number 156-02434

Type WSSDFTM8WSSDSET

Color Brown (BN)

Quantity Per pack

Product Description These two-piece fasteners are pre-assembled and offer a simple and versatile method of bundling and mounting cables. Sold as an unassembled set, this oval fir tree and tie combination allows the user to install the tie in two different directions, securing the bundle perpendicular or inline to the oval mounting hole.

Short Description 2-Piece Cable Tie with Fir Tree Mount, 6.5mm Hole and M8 Threaded Hole, PA46, Brown, 1200/ctn

Global Part Name

WSSDFTM8WSSDSET-PA46-BN

Minimum Tensile Strength (Imperial)

120

Minimum Tensile Strength (Metric)

533

Length L (Imperial)

9.1

Length L (Metric)

231.14

Fixation Method

Fir tree for round holes

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.88

Width W (Metric)

22.6

Bundle Diameter Min (Imperial)

0.37

Bundle Diameter Min (Metric)

9.4

Bundle Diameter Max (Imperial)

2.25

Bundle Diameter Max (Metric)

57.15

Height H (Imperial)	0.89
Height H (Metric)	22.77
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.23
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.28 "
Mounting Hole Diameter D (Metric)	M8 Threaded 6.1 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.0
Material	Polyamide 4.6 (PA46)
Foot Part Material	PA46
Material Shortcut	PA46
Flammability	UL 94 V-2

Halogen Free	Yes
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +266°F (-40°C to +130°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	1200
Package Quantity (Metric)	1200
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)