

## Specification Sheet

Part Number: 156-02835



Multi-option dual clip stud mount secures two bundles running alongside a bolt or stud.

Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.

Controlled flex and angled entry promote easy installation.

Article Number	156-02835
Type	SMF2MOC12MX2
Color	Black (BK)
Quantity Per	bag
Product Description	The dual MOC with stud mount features two of HellermannTyton's unique retention clips with a best-in-class stud mount to secure to a 5mm or 6mm stud or bolt. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point.
Short Description	Dual Clip Stud Mount to MOC Clip, 12mm Clip, 5mm/6mm Stud Mount, PA66HIRHSUV, Black, 1000/ctn
Global Part Name	SMF2MOC12MX2-PA66HIRHSUV-BK

Length L (Imperial)	2.52
Length L (Metric)	63.9
Fixation Method	Stud Mount
Releasable Closure	No
Bundle Diameter Min (Imperial)	0.41
Bundle Diameter Min (Metric)	10.5
Bundle Diameter Max (Imperial)	0.54
Bundle Diameter Max (Metric)	13.8
Height H (Imperial)	1.20
Height H (Metric)	30.5
Depth D (Imperial)	0.61
Depth D (Metric)	15.5
Nominal Diameter (Imperial)	0.47
Nominal Diameter (Metric)	12.0
Stud Diameter (Metric)	5.0 mm 6.0 mm
Stud Diameter (Imperial)	0.20 ";0.24

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	2000
Customs Number	3926909988

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

