

## Specification Sheet

Part Number: 156-02836



Multi-option dual clip stud mount secures two bundles running alongside a bolt or stud.

Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.

Controlled flex and angled entry promote easy installation.

Dual Clip Stud Mount to MOC Clip, 16mm Clip, 5mm/6mm Stud Mount, PA66HIRHSUV, Black, 1000/ctn

Article Number 156-02836

Type SMF2MOC16MX2

Color Black (BK)

Quantity Per pack

Product Description The dual MOC with stud mount features two of HellermannTyton's unique retention clips with a best-in-class stud mount to secure to a 5mm or 6mm stud or bolt. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point.

Short Description Dual Clip Stud Mount to MOC Clip, 16mm Clip, 5mm/6mm Stud Mount, PA66HIRHSUV, Black, 1000/ctn

Global Part Name SMF2MOC16MX2-PA66HIRHSUV-BK

Length L (Imperial)	2.83
Length L (Metric)	72.0
Fixation Method	Stud Mount
Releasable Closure	No
Bundle Diameter Min (Imperial)	0.55
Bundle Diameter Min (Metric)	14.0
Bundle Diameter Max (Imperial)	0.72
Bundle Diameter Max (Metric)	18.3
Height H (Imperial)	1.26
Height H (Metric)	32.1
Depth D (Imperial)	0.61
Depth D (Metric)	15.5
Stud Diameter (Metric)	5.0 mm 6.0 mm
Stud Diameter (Imperial)	0.20 ";0.24

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)