

## Specification Sheet

Part Number: 156-02843

Multi-option dual-clamp stud mount secures two bundles running alongside a bolt or stud.

The 360-degree locking enclosure and cable tie dynamically fit a range of bundle sizes.

Clamp can be opened for bundle maintenance.

Independent rotation allows for adjustable routing orientation.

High-performance stud mount design allows for easy installation and delivers outstanding stud retention to keep bundles secure.



Dual Clip Stud Mount to LOC Locking Clamp, 10-14mm Clamp, 5mm/6mm Std Mount, PA66HIRHSUV, Bk, 1000/ctn

Article Number 156-02843

Type SMF2LOC10-14X2

Color Black (BK)

Quantity Per pack

Product Description The dual LOC with stud mount features two of HellermannTyton's locking option clamps with a best-in-class stud mount to secure to a 5mm or 6mm stud or bolt. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point.

Short Description	Dual Clip Stud Mount to LOC Locking Clamp, 10-14mm Clamp, 5mm/6mm Std Mount, PA66HIRHSUV, Bk, 1000/ctn
Global Part Name	SMF2LOC10-14X2-PA66HIRHSUV-BK
Length L (Imperial)	4.22
Length L (Metric)	107.3
Fixation Method	Stud Mount
Releasable Closure	No
Bundle Diameter Min (Imperial)	0.39
Bundle Diameter Min (Metric)	10.0
Bundle Diameter Max (Imperial)	0.59
Bundle Diameter Max (Metric)	15.0
Height H (Imperial)	1.37
Height H (Metric)	34.9
Depth D (Imperial)	0.61
Depth D (Metric)	15.5
Nominal Diameter (Imperial)	0.47
Nominal Diameter (Metric)	12.0

Mounting Hole Diameter D (Metric)	5.0 mm 6.0 mm
Stud Diameter (Metric)	6.0 mm 5.0 mm
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)