

## Specification Sheet

Part Number: 156-02879

MOC stud mount secures bundles above a bolt or stud.

Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.

Controlled flex and angled entry promote easy installation.

Independent rotation allows for adjustable routing orientation.

High-performance stud mount design allows for easy installation and delivers outstanding stud retention to keep bundles secure.



Stud Mount to MOC Clip, 10mm Clip Above Mount, 5mm/6mm Stud Mount, PA66HIRHSUV, Black, 2000/ctn

Article Number 156-02879

Type SMFMOC10M

Color Black (BK)

Quantity Per pack

Product Description The MOC with stud mount features HellermannTyton's unique retention clip with a best-in-class stud mount to secure to a 5mm or 6mm stud or bolt. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point.

|                                |   |
|--------------------------------|---|
| Short Description              | Stud Mount to MOC Clip, 10mm Clip Above Mount, 5mm/6mm Stud Mount, PA66HIRHSUV, Black, 2000/ctn |
| Global Part Name               | SMFMOC10M-PA66HIRHSUV-BK  |
| Length L (Imperial)            | 0.77  |
| Length L (Metric)              | 19.6  |
| Fixation Method                | Stud Mount  |
| Bundle Diameter Min (Imperial) | 0.37  |
| Bundle Diameter Min (Metric)   | 9.5   |
| Bundle Diameter Max (Imperial) | 0.45  |
| Bundle Diameter Max (Metric)   | 11.5  |
| Height H (Imperial)            | 1.50  |
| Height H (Metric)              | 38  |
| Depth D (Imperial)             | 0.59  |
| Depth D (Metric)               | 15.0  |
| Nominal Diameter (Metric)      | 10.0  |
| Stud Diameter (Metric)         | 5.0 mm 6.0 mm   |
| Stud Diameter (Imperial)       | 0.20 ";0.24   |

|                              |  |
|------------------------------|--|
| Material                     | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut            | PA66HIRHSUV  |
| Flammability                 | UL 94 HB   |
| Halogen Free                 | Yes  |
| UV Resistant (Yes/No)        | Yes  |
| Use Conditions               | For Indoor and Outdoor Use   |
| Operating Temperature        | -40°F to +221°F (-40°C to +105°C)  |
| Reach Compliant (Article 33) | Yes  |
| Package Quantity (Imperial)  | 2000   |
| Package Quantity (Metric)    | 2000   |
| Customs Number               | 3926909988   |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)