

Specification Sheet

Part Number: 157-00196



All-in-one bundling and fastening solution reduces costs and assembly time.

Variety of fir tree diameters and offset lengths address most offset applications.

High-spec materials and superior design deliver excellent performance and value.

1-Piece Cable Tie with Offset Fir Tree with Disc, 25 mm, FT6, 9.6"L, 7.6 - 8.4 mm Hole, PA66HIRHSUV, Black, 500/pkg

Article Number 157-00196

Type T50ROSFT825SO

Color Black (BK)

Quantity Per pack

Product Description

Offset cable ties route and position bundles away from a mounting hole. Rigid offset bar eliminates potential bending of wire or cables once installed. Multiple offset distances and fir tree sizes cover the majority of industry offset applications. The tie strap's outside serration design provides a smooth surface to protect soft bundles. HellermannTyton's one-piece mounting ties offer a complete solution by both bundling and mounting. Their ideal combination of high-specification materials and superior design suit the needs of complex applications.

Short Description

1-Piece Cable Tie with Offset Fir Tree with Disc, 25 mm, FT6, 9.6"L, 7.6 - 8.4 mm Hole, PA66HIRHSUV, Black, 500/pkg

Global Part Name

T50ROSFT825SO-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

50

Minimum Tensile Strength (Metric)

225

Length L (Imperial)

9.6

Length L (Metric)

245.1

Offset Length (Imperial)

0.98

Offset Length (Metric)

25.0

Fixation Method

Fir tree for round holes

Identification Plate Position

none

Releasable Closure

No

Width W (Imperial)

0.20

Width W (Metric)

5.1

Bundle Diameter Min (Imperial)

0.08

Bundle Diameter Min (Metric)

2.0

Bundle Diameter Max (Imperial)

1.97

Bundle Diameter Max (Metric)

50.0

| | |
|-----------------------------------------|--------------------------------------------------------------------------|
| Panel Thickness Min (Imperial) | 0.02 |
| Panel Thickness Max (Imperial) | 0.24 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 6.0 |
| Mounting Hole Diameter D (Imperial) | 0.30 - 0.33 " |
| Mounting Hole Diameter D (Metric) | 7.6 - 8.4 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.3 |
| Mounting Hole Diameter D Max (Imperial) | 0.33 |
| Mounting Hole Diameter D Max (Metric) | 8.4 |
| Disc Diameter (Metric) | 19.0 |
| Disc Diameter (Imperial) | 0.75 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| UV Resistant (Yes/No) | Yes |
| Use Conditions | For Indoor and Outdoor Use |

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Operating Temperature intermittent, 1000 hours +320°F (+160°C)

Operating Temperature intermittent, 5000 hours +257°F (+125°C)

Operating Temperature intermittent, 500 hours +329°F (+165°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)