


Specification Sheet

Part Number: 157-00328



Offset design positions bundles away from obstructions, heat or sources of abrasion.

Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.

PA46 material option allows use in high-heat applications.

Offset M8 Stud Mount Tie, 7.5" Tie, 25.5 mm Offset, 50lb Tensile Strength, PA46, Brown, 1500/pkg

Article Number 157-00328

Type T50ROSM8SMSO25

Color Brown (BN)

Quantity Per pack

Product Description This mount features an offset design, which positions bundles away from obstructions, heat or sources of abrasion. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. Available in standard and high-heat material options.

Short Description Offset M8 Stud Mount Tie, 7.5" Tie, 25.5 mm Offset, 50lb Tensile Strength, PA46, Brown, 1500/pkg

Global Part Name T50ROSM8SMSO25-PA46-BN

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 223

Length L (Imperial) 8.9

Length L (Metric) 226.14

Offset Length (Imperial) 1.0

Offset Length (Metric) 25.5

Fixation Method Stud Mount

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Width W (Imperial) 0.70

Width W (Metric) 17.75

Bundle Diameter Min (Imperial) 0.08

Bundle Diameter Min (Metric) 2.0

Bundle Diameter Max (Imperial) 1.97

| | |
|-------------------------------------|-----------------------------------|
| Bundle Diameter Max (Metric) | 50.0 |
| Cable Ties | 157-00328 |
| Height H (Imperial) | 0.59 |
| Height H (Metric) | 15.0 |
| Mounting Hole Diameter D (Imperial) | 0.31 x 0.05 " |
| Mounting Hole Diameter D (Metric) | M8 x 1.25 |
| Stud Diameter (Metric) | 8.0 mm |
| Stud Diameter (Imperial) | 0.31 |
| Material | Polyamide 4.6 (PA46) |
| Material Shortcut | PA46 |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor Use Only |
| Operating Temperature | -40°F to +266°F (-40°C to +130°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |

| | |
|-----------------------------|------------|
| Package Quantity (Imperial) | 1500 |
| Package Quantity (Metric) | 1500 |
| Customs Number | 3926909988 |

7930 N. Faulkner Road, Milwaukee, WI 53224
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)