

Specification Sheet

Part Number: 157-00338

Offset design positions bundles away from obstructions, heat or sources of abrasion.

Low profile head allows mounts to stack, providing more mounting versatility from a single stud.

Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.

PA46 material option allows use in high-heat applications..



Offset Low-Profile M6/M5 Stud Mount Tie, 7.5" Tie, 50lb Tensile Strength, PA46, Brown, 3000/pkg

Article Number 157-00338

Type T50ROSLPM6SMSO25

Color Brown (BN)

Quantity Per pack

Product Description One-piece cable tie with stud mount features an offset design to position bundles away from obstructions, heat or sources of abrasion. It includes a low-profile head, allowing multiple tie mounts to be stacked on a single bolt and providing space savings in tight areas. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. Available in standard and high-heat material options.

| | |
|-------------------------------------|---|
| Short Description | Offset Low-Profile M6/M5 Stud Mount Tie, 7.5" Tie, 50lb Tensile Strength, PA46, Brown, 3000/pkg |
| Global Part Name | T50ROSLPM6SMSO25-PA46-BN |
| Minimum Tensile Strength (Imperial) | 50 |
| Minimum Tensile Strength (Metric) | 225 |
| Length L (Imperial) | 8.8 |
| Length L (Metric) | 223.52 |
| Offset Length (Imperial) | 1.0 |
| Offset Length (Metric) | 25.5 |
| Fixation Method | Stud Mount |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Width W (Imperial) | 0.56 |
| Width W (Metric) | 14.2 |
| Bundle Diameter Min (Imperial) | 0.08 |
| Bundle Diameter Min (Metric) | 2.0 |

| | |
|-------------------------------------|-----------------------------------|
| Bundle Diameter Max (Imperial) | 1.97 |
| Bundle Diameter Max (Metric) | 50.0 |
| Height H (Imperial) | 0.25 |
| Height H (Metric) | 6.30 |
| Mounting Hole Diameter D (Imperial) | 0.24 x 0.04 " |
| Mounting Hole Diameter D (Metric) | M6 x 1 |
| Stud Diameter (Metric) | 5.0 mm 6.0 mm |
| Stud Diameter (Imperial) | 0.20 ", 0.24 |
| Material | Polyamide 4.6 (PA46) |
| Material Shortcut | PA46 |
| Flammability | UL 94 V-2 |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor Use Only |
| Operating Temperature | -40°F to +266°F (-40°C to +130°C) |

| | |
|------------------------------|------------|
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 3000 |
| Package Quantity (Metric) | 3000 |
| Customs Number | 3926909988 |

7930 N. Faulkner Road, Milwaukee, WI 53224
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)