

## Specification Sheet

Part Number: 157-00359



All-in-one bundling and fastening solution reduces costs and assembly time.

Disc feature provides anti-rattle protection in high-vibration applications.

1-Piece Cable Tie with Fir Tree Mount with Disc, 6.5"L, 0.25 - 0.28" Mounting Hole, PA66HS, Black, 500/bg

Article Number 157-00359

Type T50SOSFT6.5LG-E4X

Color Black (BK)

Quantity Per pack

Product Description One-piece mounting ties offer a complete solution by both bundling and mounting wires, cables and tubes. The fir tree mount provides low insertion force with a high extraction force. Outside serrations on the cable tie leave a smooth interior surface that's gentler on sensitive wire insulation. The unique head design allows the cable tie to firmly hold bundles as small as .06" diameter. The disc offers added protection against debris.

Short Description 1-Piece Cable Tie with Fir Tree Mount with Disc, 6.5"L, 0.25 - 0.28" Mounting Hole, PA66HS, Black, 500/bg

Global Part Name T50SOSFT6.5LG-E4X-PA66HS-BK

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 6.5

Length L (Metric) 165.0

Fixation Method Fir tree for round holes

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Width W (Imperial) 0.18

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.04

Bundle Diameter Min (Metric) 1.0

Bundle Diameter Max (Imperial) 1.38

Bundle Diameter Max (Metric) 35.0

Thickness T (Imperial) 0.05

|   |  |
|---|--|
| Thickness T (Metric)                    | 1.3                                    |
| Panel Thickness Min (Imperial)          | 0.03                                   |
| Panel Thickness Max (Imperial)          | 0.28                                   |
| Panel Thickness Min (Metric)            | 0.7                                    |
| Panel Thickness Max (Metric)            | 7.0                                    |
| Mounting Hole Diameter D (Imperial)     | 0.25 - 0.28 "                          |
| Mounting Hole Diameter D (Metric)       | 6.3 - 7.0 mm                           |
| Mounting Hole Diameter D Min (Imperial) | 0.25                                   |
| Mounting Hole Diameter D Max (Imperial) | 0.28                                   |
| Mounting Hole Diameter D Max (Metric)   | 7.0                                    |
| Disc Diameter (Metric)                  | 16.0                                   |
| Disc Diameter (Imperial)                | 0.63                                   |
| Material                                | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut                       | PA66HS                                 |
| Flammability                            | UL 94 HB                               |

|                              |                                   |
|------------------------------|-----------------------------------|
| UV Resistant (Yes/No)        | No                                |
| Use Conditions               | For Indoor and Outdoor Use        |
| Operating Temperature        | -40°F to +257°F (-40°C to +125°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Package Quantity (Imperial)  | 500                               |
| Package Quantity (Metric)    | 500                               |
| Customs Number               | 3926909988                        |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Privacy Policy](#)   [Cookie Policy](#)   [Terms and Conditions](#)