

Specification Sheet

Part Number: 157-00402

Mount provides low insertion and high extraction forces which makes for a strong and easy installation.

Tie utilizes a strong hinge between the stud mount and strap head to provide superior holding ability.

Clamping rails increase grip on round bundles.

Thinner strap provides increased flexibility for improved ergonomics.



Wide Strap Cable Tie with .25" Stud Mount, 15.7" Long, 0.5" Wide, PA66HIRHSUV, Black, 300/bg

Article Number 157-00402

Type WSR250

Color Black (BK)

Quantity Per pack

Product Description The Wide Strap Stud Mount Cable Tie minimizes pinching on soft bundles and features a low profile head to provide compact bundling. A thinner strap provides increased flexibility for improved ergonomics. Available in various stud mount sizes, the wide strap tie utilizes a strong hinge between the stud mount and head to provide superior holding ability on a threaded stud.

| | |
|-------------------------------------|--|
| Short Description | Wide Strap Cable Tie with .25" Stud Mount, 15.7" Long, 0.5" Wide, PA66HIRHSUV, Black, 300/bg |
| Global Part Name | WSR250-PA66HIRHSUV-BK |
| Minimum Tensile Strength (Imperial) | 120 |
| Minimum Tensile Strength (Metric) | 535 |
| Length L (Imperial) | 15.7 |
| Length L (Metric) | 398.8 |
| Fixation Method | Stud Mount |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.5 |
| Width W (Metric) | 12.7 |
| Bundle Diameter Min (Imperial) | 0.37 |
| Bundle Diameter Min (Metric) | 9.5 |
| Bundle Diameter Max (Imperial) | 4.13 |

| | |
|--|--|
| Bundle Diameter Max (Metric) | 105.0 |
| Thickness T (Imperial) | 0.06 |
| Thickness T (Metric) | 1.4 |
| Stud Diameter (Metric) | M6 |
| Stud Diameter (Imperial) | 1/4 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL 94 HB |
| UV Resistant (Yes/No) | Yes |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Operating Temperature intermittent, 1000 hours | +320°F (+160°C) |
| Operating Temperature intermittent, 5000 hours | +257°F (+125°C) |
| Operating Temperature intermittent, 500 hours | +329°F (+165°C) |
| Reach Compliant (Article 33) | Yes |

ROHS Compliant Yes

Package Quantity (Imperial) 300

Package Quantity (Metric) 300

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)