

Specification Sheet

Part Number: 166-90182

Integrated flip open lid for quick and easy assembly.

Inner rib prevents conduit from slipping.

Easy access mounting hole reduces installation time.

Quick release for easy future access.



HelaGuard® PACC Conduit Clip, 1.25" Dia, PA66, Black, 5/pkg

|                     |                                                                                                                                                                          |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 166-90182                                                                                                                                                                |
| Type                | PACC1250                                                                                                                                                                 |
| Color               | Black (BK)                                                                                                                                                               |
| Quantity Per        | pack                                                                                                                                                                     |
| Product Description | Conduit Clips clamp onto corrugated conduits and tubing to secure. Nylon material resists corrosion and chemicals. Conduit clips can also be used on C-shaped DIN rails. |
| Short Description   | HelaGuard® PACC Conduit Clip, 1.25" Dia, PA66, Black, 5/pkg                                                                                                              |
| Global Part Name    | PACC1250-PA66-BK                                                                                                                                                         |

|                     |      |
|---------------------|------|
| Length L (Imperial) | 2.24 |
|---------------------|------|

|                   |    |
|-------------------|----|
| Length L (Metric) | 57 |
|-------------------|----|

|         |      |
|---------|------|
| Variant | Clip |
|---------|------|

|                    |      |
|--------------------|------|
| Width W (Imperial) | 0.59 |
|--------------------|------|

|                  |    |
|------------------|----|
| Width W (Metric) | 15 |
|------------------|----|

|                     |      |
|---------------------|------|
| Height H (Imperial) | 2.36 |
|---------------------|------|

|                   |    |
|-------------------|----|
| Height H (Metric) | 60 |
|-------------------|----|

|                             |      |
|-----------------------------|------|
| Nominal Diameter (Imperial) | 1.25 |
|-----------------------------|------|

|                           |    |
|---------------------------|----|
| Nominal Diameter (Metric) | 42 |
|---------------------------|----|

|                                     |        |
|-------------------------------------|--------|
| Mounting Hole Diameter D (Imperial) | 0.24 " |
|-------------------------------------|--------|

|                                   |        |
|-----------------------------------|--------|
| Mounting Hole Diameter D (Metric) | 6.0 mm |
|-----------------------------------|--------|

|                                       |   |
|---------------------------------------|---|
| Mounting Hole Diameter D Max (Metric) | 6 |
|---------------------------------------|---|

|          |                      |
|----------|----------------------|
| Material | Polyamide 6.6 (PA66) |
|----------|----------------------|

|                   |      |
|-------------------|------|
| Material Shortcut | PA66 |
|-------------------|------|

|              |           |
|--------------|-----------|
| Flammability | UL 94 V-2 |
|--------------|-----------|

|                              |                                   |
|------------------------------|-----------------------------------|
| Halogen Free                 | Yes                               |
| UV Resistant (Yes/No)        | No                                |
| Use Conditions               | For Indoor and Outdoor Use        |
| Operating Temperature        | -58°F to +275°F (-50°C to +135°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Package Quantity (Imperial)  | 10                                |
| Package Quantity (Metric)    | 10                                |
| Customs Number               | 3926909988                        |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Privacy Policy](#)   [Cookie Policy](#)   [Terms and Conditions](#)