

## Specification Sheet

Part Number: 166-90987



Overlapping conduit design increases mechanical protection and eliminates unintentional exposure of wires caused by motion, vibration or when routed around corners.

Material is easy to use and cut - reduces installation time and labor costs.

Good impact strength; recovers quickly if crushed.

HelaGuard® Non-Metallic Conduit, Double Slit, 1.25" Dia, PP, Black, 82 ft/Std. Reel

Article Number 166-90987

Type HG-DC1250

Color Black (BK)

Quantity Per pack

Product Description A standard-weight, polypropylene, corrugated two-piece conduit, each of which is slit open to ease installation and maintenance of wire and cable bundles. The interlocking construction is excellent for retrofitting projects. Polypropylene material is typically used in building construction, particularly where buried in concrete or plaster. Flexible, abrasion resistant and durable for a variety of applications.

Short Description HelaGuard® Non-Metallic Conduit, Double Slit, 1.25" Dia, PP, Black, 82 ft/Std. Reel

|                                |                            |
|--------------------------------|----------------------------|
| Global Part Name               | HG-DC1250-PP-BK            |
| Length L (Imperial)            | 82.0                       |
| Length L (Metric)              | 25                         |
| Inner Diameter D (Imperial)    | 1.26                       |
| Inner Diameter D (Metric)      | 32                         |
| Outside Diameter OD (Imperial) | 1.68                       |
| Outside Diameter OD (Metric)   | 42.5                       |
| Nominal Diameter (Imperial)    | 1.25                       |
| Nominal Diameter (Metric)      | 42                         |
| Material                       | Polypropylene (PP)         |
| Material Shortcut              | PP                         |
| Flammability                   | EN IEC 61386               |
| Halogen Free                   | No                         |
| UV Resistant (Yes/No)          | No                         |
| Use Conditions                 | For Indoor and Outdoor Use |

Operating Temperature -4°F to +194°F (-20°C to +90°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 82

Package Quantity (Metric) 25

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)