

Specification Sheet

Part Number: CTP120STDUNSLIT



Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture

Tubing protects cables and wires against automotive fluids, vibration wear

Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight

Nylon material is formulated to withstand high temperatures

Convoluted Tubing, Unslit, 0.5" Dia, PE, Black, 1000 ft/ctn

Article Number	169-60539
Type	CTP120UNSLIT
Color	Black (BK)
Quantity Per	carton
Product Description	HellermannTyton’s Convoluted Tubing, also known as Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
Short Description	Convoluted Tubing, Unslit, 0.5" Dia, PE, Black, 1000 ft/ctn

Global Part Name	CTP120UNSLIT-PE-BK
------------------	--------------------

Length L (Imperial)	1000.0
---------------------	--------

Length L (Metric)	304.8
-------------------	-------

Variant	Unslit
---------	--------

Bundle Diameter Min (Imperial)	0.1
--------------------------------	-----

Bundle Diameter Min (Metric)	1.0
------------------------------	-----

Bundle Diameter Max (Imperial)	0.51
--------------------------------	------

Bundle Diameter Max (Metric)	13.1
------------------------------	------

Inner Diameter D (Imperial)	0.516
-----------------------------	-------

Inner Diameter D (Metric)	13.11
---------------------------	-------

Diameter D (Imperial)	0.70
-----------------------	------

Diameter D (Metric)	17.78
---------------------	-------

Outside Diameter OD (Imperial)	0.70
--------------------------------	------

Outside Diameter OD (Metric)	17.78
------------------------------	-------

Nominal Diameter (Imperial)	0.5
-----------------------------	-----

Nominal Diameter (Metric)	12.70
---------------------------	-------

Wall Thickness WT (Imperial)	0.005
Wall Thickness WT (Metric)	0.127
Material	Polyethylene (PE)
Material Shortcut	PE
Flammability	Not Flame Retardant
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	304.80
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)