

Specification Sheet

Part Number: 170-03217

Split wrap design needs no fasteners and installs quickly, saving assembly time and future accessibility without disassembly.

Bends to a tight radius without distortion or splitting open.

Unique construction retains shape and rigidity throughout unrolling.

Added flame-inhibitor fibers extinguish quickly and reduces potential flame spread to surrounding components.

Easy open design allows quick access and ability to apply protective sleeving post assembly or post installation situations.



Braided Sleeving, Split Wrap Woven, Flame Retardant, 3/8" Dia, PET, Black, 250 ft/bulk reel

Article Number	170-03217
Type	BSSWVFR380B
Color	Black (BK)
Quantity Per	pack

Product Description	A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires. More flexible than spiral wraps or convoluted tubing, this product is a fast and easy option for adding protection in post-assembly or post-installation applications. Meets NFPA 130 rail market applications.
Short Description	Braided Sleeving, Split Wrap Woven, Flame Retardant, 3/8" Dia, PET, Black, 250 ft/bulk reel
Global Part Name	BSSWVFR380B-PET-BK
Length L (Imperial)	250.0
Length L (Metric)	76.2
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	0.37
Bundle Diameter Max (Metric)	9.5
Diameter D (Imperial)	0.38
Diameter D (Metric)	9.5
Nominal Diameter (Imperial)	0.38
Nominal Diameter (Metric)	9.5

Wall Thickness WT (Imperial)	0.027
Wall Thickness WT (Metric)	0.68
Material	Polyester (PET)
Material Shortcut	PET
Flammability	UL VW-1
Halogen Free	Yes
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-94°F to +257°F (-70°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	ASTM 1354 ASTM E 162 ASTM E 662 Exova NFPA130: 2017
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	250

Package Quantity (Metric) 76.20

Customs Number 5806322000

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)