

Specification Sheet

Part Number: 184-44002

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High-Density Slotted Wall Wiring Duct, 4 x 4", 6 ft Sticks, Non-Adhesive, PVC, Gray, 60ft/ctn

Article Number 184-44002

Type SLHD4X4

Color Gray (GY)

Quantity Per carton

Product Description HellermannTyton High-Density Slotted Wall Wiring Duct features narrow fingers equaling a 2-to-1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

| | |
|----------------------------------|---|
| Short Description | High-Density Slotted Wall Wiring Duct, 4 x 4", 6 ft Sticks, Non-Adhesive, PVC, Gray, 60ft/ctn |
| Global Part Name | SLHD4X4-PVC-GY |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 1.83 |
| Fixation Method | Non-Adhesive |
| Width W (Imperial) | 4.0 |
| Width W (Metric) | 101.6 |
| Height H (Imperial) | 4.07 |
| Height H (Metric) | 103.4 |
| Mounting Hole Centers (Imperial) | 2.0 |
| Material | Polyvinylchloride (PVC) |
| Material Shortcut | PVC |
| Flammability | UL 94 V-0 |
| Halogen Free | No |

| | |
|------------------------------|--|
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor Use Only |
| Operating Temperature | +122°F (+50°C) |
| Reach Compliant (Article 33) | No |
| ROHS Compliant | Yes |
| Certification/Specification | EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A CSA UL |
| UL Recognized (US) | Yes |
| Package Quantity (Imperial) | 60.0 |
| Package Quantity (Metric) | 18.3 |
| Customs Number | 3925900000 |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)