

## Specification Sheet

Part Number: TSRPFW-RB

Pre-scored knockouts on the base and all four sides remove easily to accomodate all HellermannTyton TSR/TSRP raceway sizes.

Simple two-piece design is easy to install and includes foam tape backing with rubber based adhesive to assist with temporary positioning and mounting.

Accommodates a variety of alarm/detector and fixture makes and models.

PVC construction is lightweight and durable.

Covers are designed to overlap raceway mating points to hide uneven cuts.

Fittings incorporate a minimum 1" bend radius per TIA/EIA 568-B and 569-A standards.

UL 5A Listed to 600V and CSA Certified to 300V (not to exceed 10 lbs. per UL and 5 lbs. per CSA.)



Round Junction pkg, 1-1/4" Deep, PVC, Office White, 1/bg

|                |                     |
|----------------|---------------------|
| Article Number | 250-00210           |
| Type           | TSRP-RB             |
| Color          | Office White (OEWH) |
| Quantity Per   | pack                |

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | Designed for mounting of low and line voltage fixtures such as hanging lights, smoke detectors, carbon monoxide detectors and security cameras, the TSRP round junction box complements HellermannTyton's full line of power rated TSRP and low voltage TSR raceway systems. The TSRP round junction box is constructed of a durable PVC material and is available in white, office white and ivory to coordinate with all HellermannTyton surface mount raceway systems. |
| Short Description   | Round Junction pkg, 1-1/4" Deep, PVC, Office White, 1/bg                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Global Part Name    | TSRP-RB-PVC-WH                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Length L (Imperial) | 5.25                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Length L (Metric)   | 133.35                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Width W (Imperial)  | 5.25                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Width W (Metric)    | 133.35                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Height H (Imperial) | 1.25                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Height H (Metric)   | 31.75                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Material            | Polyvinylchloride (PVC)                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Material Shortcut   | PVC                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Flammability        | UL 94 V-0                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Halogen Free        | No                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

|                              |                     |
|------------------------------|---------------------|
| UV Resistant (Yes/No)        | No                  |
| Use Conditions               | For Indoor Use Only |
| Operating Temperature        | +122°F (+50°C)      |
| Reach Compliant (Article 33) | No                  |
| ROHS Compliant               | Yes                 |
| UL Listed (US and Canada)    | Yes                 |
| UL Listed (US)               | Yes                 |
| Package Quantity (Imperial)  | 1                   |
| Package Quantity (Metric)    | 1                   |
| Customs Number               | 3925900000          |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Privacy Policy](#)   [Cookie Policy](#)   [Terms and Conditions](#)