

## Specification Sheet

Part Number: TSRP1FW-6A

Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance.

U.L. Listed for power up to 600 Volts, meeting UL5A and CSA 22.2 Number 62-93 Standards.

Manufactured from UL 94V-0 rated PVC material.

Fittings incorporate a minimum 1" bend radius per TIA/EIA 568-B and 569-A standards.

Large base for greater adhesive surface.

Rubber-based foam tape adhesive with high ultimate bond strength, which conforms to any surface.

Flexible hinge allows the raceway to endure numerous openings without creating discoloration or stress cracking.

Junction boxes can be used for electrical or data outlets.

Designed to complement HellermannTyton's industry standard TSR low voltage raceway system.



One Piece Power Rated Raceway, 3/4", 6 ft Sticks, PVC, Office White, 120ft/ctn

Article Number 250-61600

Type TSRP1-6A

Color Office White (OEWH)

|                     |  |
|---------------------|--|
| Quantity Per        | carton   |
| Product Description | One Piece Power Rated Raceway, 3/4", 6 ft Sticks, PVC, Office White, 120ft/ctn |
| Short Description   | One Piece Power Rated Raceway, 3/4", 6 ft Sticks, PVC, Office White, 120ft/ctn |
| Global Part Name    | TSRP1-6A-PVC-WH  |
| Length L (Imperial) | 6.0  |
| Length L (Metric)   | 1.83   |
| Width W (Imperial)  | 0.75   |
| Width W (Metric)    | 19.05  |
| Height H (Imperial) | .50  |
| Height H (Metric)   | 12.70  |
| Material            | Polyvinylchloride (PVC)  |
| Material Shortcut   | PVC  |
| Flammability        | UL 94 V-0  |
| Halogen Free        | No   |

|                              |                     |
|------------------------------|---------------------|
| UV Resistant (Yes/No)        | No                  |
| Use Conditions               | For Indoor Use Only |
| Operating Temperature        | +122°F (+50°C)      |
| BABA Compliant               | YES                 |
| Reach Compliant (Article 33) | No                  |
| ROHS Compliant               | Yes                 |
| UL Listed (US and Canada)    | Yes                 |
| UL Listed (US)               | Yes                 |
| Package Quantity (Imperial)  | 120.0               |
| Package Quantity (Metric)    | 36.6                |
| Customs Number               | 3925900000          |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Privacy Policy](#)

[Cookie Policy](#)

[Terms and Conditions](#)