

Specification Sheet

Part Number: 300-30957



Tubing is 2:1, thin wall that provides protection against corrosion and mechanical abrasion.

Available in multiple colors and sizes for easy marking and handling.

Conveniently stored in a handy dispenser box for quick and easy use.

Article Number	300-30957
Type	HIS-PACK-9.5/4.7
Color	Green-Yellow (GNYE)
Quantity Per	pack
Product Description	HIS-PACK Heat Shrink is a general-purpose, thin-wall Polyolefin tubing that provides electrical insulation and protection against corrosion and mechanical abrasion. HIS-PACKs are available in multiple colors and ten sizes ranging from 1/16" (1.2mm) to 1" (25.4mm). Tubing is conveniently stored in a handy dispenser box with hang tag and is RoHS approved.
Short Description	Heat Shrink Tubing, Non-Adhesive, 2:1 Shrink Ratio, 0.37 Supp/.17" Recov Dia, PO-X, Grn/Yel, 16.4ft/pkg

Global Part Name	HIS-PACK-9.5/4.7-PO-X-GNYE
Length L (Imperial)	16.4
Length L (Metric)	5.0
Variant	Thin-Wall
Bundle Diameter Max (Imperial)	0.185
Bundle Diameter Max (Metric)	4.7
Nominal Diameter (Imperial)	0.38
Nominal Diameter (Metric)	6.4
Wall Thickness WT (Imperial)	.023
Wall Thickness WT (Metric)	0.60
Material	Polyolefin, cross-linked (PO-X)
Material Shortcut	PO-X
Flammability	UL 224 VW-1
Halogen Free	No
UV Resistant (Yes/No)	No

Operating Temperature	-67°F to +257°F (-55°C to +125°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Certification/Specification	UL ANSI/UL 224 UL CSA -C22.2 No.198.1 UL CSA -C22.1
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	16.4
Package Quantity (Metric)	5
Customs Number	3926909988
Weight (Metric)	0.181
Weight (Imperial)	0.4

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)