

Specification Sheet

Part Number: 596-00240

Made with UV-stable inks and materials for durability and weather resistance.

Reflective properties to meet applicable NEC® code requirements for reflective identification.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

|                                |  |
|--------------------------------|--|
| RATED AC OPERATING CURRENT     |  |
| MAX RATED AC OPERATING CURRENT |  |
| RATED AC OPERATING VOLTAGE     |  |
| MAX RATED AC OPERATING VOLTAGE |  |
| RATED SHORT CIRCUIT CURRENT    |  |
| MAXIMUM SYSTEM VOLTAGE         |  |

Article Number 596-00240

Type ACRATING

Color Red (RD)

Quantity Per pack

Product Description Designed with cross-laminated UV stable materials, these variable print Solar Installation Labels are designed to accept printing from any standard thermal transfer printer using a resin-based ink ribbon for the best durability. Print your voltage information directly on the label and then laminate with an optional clear acrylic laminate material for added protection. These labels can be used to print disconnecting means and breaker series directly on the labels for a more professional result and a smoother inspection process.

|                                |                                                                            |
|--------------------------------|----------------------------------------------------------------------------|
| Short Description              | Solar Label, Printable, DC BACKUP SYSTEM, 4.0" x 2.0", PET, Red, 50/roll   |
| Global Part Name               | ACRATING-840/281-RD                                                        |
| Width W (Imperial)             | 4.0                                                                        |
| Width W (Metric)               | 101.6                                                                      |
| Thickness T (Imperial)         | 0.0025                                                                     |
| Thickness T (Metric)           | 64.0                                                                       |
| Height H (Imperial)            | 2.0                                                                        |
| Height H (Metric)              | 50.8                                                                       |
| Material                       | Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281) |
| Material Shortcut              | 840/281                                                                    |
| Adhesive                       | Acrylic                                                                    |
| Halogen Free                   | Yes                                                                        |
| UV Resistant (Yes/No)          | Yes                                                                        |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C)                                          |

|                              |                                                           |
|------------------------------|-----------------------------------------------------------|
| Operating Temperature        | -40°F to +302°F (-40°C to +150°C)                         |
| Reach Compliant (Article 33) | Yes                                                       |
| ROHS Compliant               | Yes                                                       |
| Certification/Specification  | NEC2020 IFC 2012 NEC2017 UL 969 CSA 66956 NEC2014 NEC2023 |
| Warranty (US)                | Yes                                                       |
| UL Recognized (US)           | Yes                                                       |
| Package Quantity (Imperial)  | 50                                                        |
| Package Quantity (Metric)    | 50                                                        |
| Customs Number               | 3919102055                                                |
| Labels per Column            | 1                                                         |
| Labels per Row               | 1                                                         |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com