

## Specification Sheet

Part Number: TAG73T1-822



White polyester is glossy, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Thermal Transfer Adhesive Labels, 2.0 x 1.0", 1 Across, Polyester, White, 3000/roll

Article Number 596-73822

Type TAG73T1

Color White (WH)

Quantity Per pack

Product Description HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 822 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature and UV resistant marking.

Short Description Thermal Transfer Adhesive Labels, 2.0 x 1.0", 1 Across, Polyester, White, 3000/roll

|                                |                                   |
|--------------------------------|-----------------------------------|
| Global Part Name               | TAG73T1-822-WH                    |
| Width W (Imperial)             | 2.0                               |
| Width W (Metric)               | 50.8                              |
| Thickness T (Metric)           | 64.0                              |
| Height H (Imperial)            | 1.0                               |
| Height H (Metric)              | 25.40                             |
| Width of Liner (Metric)        | 55.88                             |
| Width of Liner (Imperial)      | 2.2                               |
| Material                       | Type 822, Polyester (822)         |
| Material Shortcut              | 822                               |
| Adhesive                       | Acrylic                           |
| Halogen Free                   | Yes                               |
| UV Resistant (Yes/No)          | No                                |
| Use Conditions                 | For Indoor Use Only               |
| Adhesive Operating Temperature | -40°F to +248°F (-40°C to +120°C) |

Operating Temperature -40°F to +302°F (-40°C to +150°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Certification/Specification UL-Recognized

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity (Imperial) 3000

Package Quantity (Metric) 3000

Customs Number 3919102055

Labels per Column 1

Labels per Row 1

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)