

Specification Sheet

Part Number: FU25-25M

Inherently low fire hazard material can withstand extreme temperature conditions.

Highly durable spiral metallic conduit provides extra flexibility along with a high degree of compression, tensile and impact strength.

Provides ingress protection performance to IP40 when used with FU-M style fittings.

Tight bend radius for use in installations requiring constant movement or vibration.



Article Number	166-90755
----------------	-----------

Type	FU25-25M
------	----------

Color	Metal (ML)
-------	------------

Quantity Per	reel
--------------	------

Product Description	An extra flexible, galvanized steel conduit used in tight or constrained spaces. FU-X series is a helically wound, non-UL rated metallic conduit used in applications that demand higher levels of movement, vibration and bending. Designed for use where an extra flexible metallic conduit is needed in machinery for protecting hydraulic or pneumatic hoses or in elevated temperature conditions. Use with FU-M series metallic fittings for IP40 ratings.
---------------------	--

Short Description	Liquid-Tight Metallic Conduit, Extra Flexible, 0.75" (25mm) Dia, Galvanized Steel, Metal, 82ft/Reel
Global Part Name	FU25-25M-GS-ML
Diameter D (Imperial)	0.82
Diameter D (Metric)	20.9
Outside Diameter OD (Imperial)	0.97
Outside Diameter OD (Metric)	24.6
Nominal Diameter (Imperial)	0.75
Nominal Diameter (Metric)	25.0
Material	Galvanised Steel (GS)
Material Shortcut	GS
Flammability	EN IEC 61386-1
Halogen Free	Yes
UV Resistant (Yes/No)	No
Operating Temperature	-148°F to +572°F (-100°C to +300°C)

Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	82.0
Package Quantity (Metric)	25.0
Customs Number	8307100000

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)