

Specification Sheet

Part Number: T250I9X2



Engineered and manufactured for maximum performance and quality.  
Made from 100% high-quality plastic to ensure efficient recycling.  
Inside serration for a strong grip onto bundles.  
Easy application either manually or with a tensioning tool.

Heavy Duty Cable Tie, 29" Long, UL Rated, 250lb Tensile Strength, PA66, Natural, 25/pkg

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 111-25219                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Type                | T250I                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Color               | Natural (NA)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Quantity Per        | bag                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Product Description | These cable ties offer a high minimum tensile strength and have a buckle feature which allows the end of the cable tie to be tucked away if necessary. The buckle also snaps into HellermannTyton lashing tie mounts (LTM.) T-Series cable ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation. |
| Short Description   | Heavy Duty Cable Tie, 29" Long, UL Rated, 250lb Tensile Strength, PA66, Natural, 25/pkg                                                                                                                                                                                                                                                                                                                                                                                                                              |

|                                     |                      |
|-------------------------------------|----------------------|
| Global Part Name                    | T250I-PA66-NA        |
| Minimum Tensile Strength (Imperial) | 250.0                |
| Minimum Tensile Strength (Metric)   | 1115.0               |
| Length L (Imperial)                 | 29.0                 |
| Length L (Metric)                   | 730.0                |
| Identification Plate Position       | none                 |
| Releasable Closure                  | No                   |
| Variant                             | Inside Serrated      |
| Width W (Imperial)                  | 0.49                 |
| Width W (Metric)                    | 12.4                 |
| Bundle Diameter Min (Imperial)      | 0.47                 |
| Bundle Diameter Min (Metric)        | 12.0                 |
| Bundle Diameter Max (Imperial)      | 8.0                  |
| Bundle Diameter Max (Metric)        | 203.0                |
| Material                            | Polyamide 6.6 (PA66) |

|                               |                                  |
|-------------------------------|----------------------------------|
| Material Shortcut             | PA66                             |
| Flammability                  | UL 94 V-2                        |
| Halogen Free                  | Yes                              |
| UV Resistant (Yes/No)         | No                               |
| Operating Temperature         | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33)  | Yes                              |
| ROHS Compliant                | Yes                              |
| Certification/Specification   | UL 62275                         |
| UL Recognized (US)            | Yes                              |
| UL Listed (US and Canada)     | Yes                              |
| UL Recognized (US and Canada) | Yes                              |
| UL Listed (US)                | Yes                              |
| Package Quantity (Imperial)   | 25                               |
| Package Quantity (Metric)     | 25                               |
| Customs Number                | 3926909988                       |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)