

Ultra short throw LCD projector with
a suite of advanced features.



Key Features

- XGA 1024 x 768 resolution
- 2,700 ANSI lumens white/color output
- 5000:1 contrast ratio
- HDMI 2 inputs
- Accentualizer - advanced image processing
- High Dynamic Contrast Range (HDCR)
- ImageCare Technology for energy savings
- Wireless compatible
- Projector Quick Connect iOS App

1.800.HITACHI
dmd.info@hal.hitachi.com
hitachi-america.us/projectors



Hitachi's CP-AX2503 ultra short throw LCD projector is ideally suited for producing large images in limited spaces. It provides vibrant image quality with cost-effective operation. A suite of advanced features normally found only on higher end models includes High Dynamic Contrast Range (HDCR), 2 HDMI ports, and Hitachi's original technology Accentualizer that allows the projected image to appear more real by enhancing sharpness, gloss and shade. Along with its light weight and compact design, the CP-AX2503 offers Hitachi's most appreciated installation feature, "Perfect Fit", allowing time saving and ease of installation. As with all Hitachi projectors, you can expect vibrant image quality, cost-efficient operation, and long-lasting reliability. Plus, Hitachi's Intelligent Eco and Saver Modes with ImageCare combines optimal picture performance with energy savings for a lower total cost of ownership. For added peace of mind, Hitachi's CP-AX2503 is also backed by a generous 3 year warranty and our world-class service and support programs.

CP-AX2503



UNIQUE FEATURES

Accentualizer

Hitachi original technology makes pictures look more real by enhancing sharpness, gloss and shade to make pictures as clear as pictures on a flat-panel device. You can also adjust the effects by three levels according to your surroundings so that the colors of projected images are the actual colors of the objects they represent.



HDCR (High Dynamic Contrast Range)

When average projectors are used in bright rooms, the darker colors of an image deteriorate and images become unclear. Using this function, blurred images caused by room lighting or outside light sources are corrected, and an effect similar to increasing contrast occurs. This results in clear images even in bright rooms.



Cloning Function

Copy setting data from one projector to others of the same model via USB memory. Cloning not only saves almost all PJ settings such as gamma and keystone via USB memory, it saves countless hours in setup and installation.



ImageCare Technology

ImageCare is a lamp power control function that combines optimal picture performance with maximum energy savings by decreasing energy usage, improving contrast ratio and lengthening lamp life. The result is a lower total cost of ownership and decreased maintenance cost.



Intelligent Eco and Saver Modes



Automatically changes the brightness of the lamp according to the brightness level of the screen. Also, automatically changes the brightness of the lamp if there is no change in the screen image. Using ImageCare technology, these features give optimal picture performance with maximum energy savings.

Perfect Fit 2



Enables the user to adjust individual corners and sides independent of one another. Perfect Fit 2 provides vertical and horizontal digital correction of either barrel or pin cushion distortions. This feature helps correct geometric and complicated distortions. Perfect Fit 2 allows the projected image to fit correctly to the screen quickly and easily.

Projector Quick Connection App For Mobile Devices



Our iOS application offers projector control and also provides the capability to display photos, document files and web site contents. Available for iPad®, iPhone® and Android devices. Works over your LAN via your RJ-45 port or via an optional USBWL11N wireless adapter.

Tabletop Presentation



Make any tabletop a projection screen using the optional tabletop stand. Ideal for a small group environment or in a room with limited space.


HI0259-Rev.1-04/14

All specifications subject to change without notice.
3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.
©2014 Hitachi America, Ltd. All Rights Reserved.

STANDARD FEATURES

Input Source Naming

Users can name input sources in simple language instead of factory default names.



Microphone Input

A microphone can be used via the jack located on the input panel. Allows for more dynamic presentations even in standby mode.



Network Control, Maintenance and Security

Embedded networking gives you the ability to manage and control multiple projectors over your LAN. Features include scheduling of events, centralized reporting, image transfer and e-mail alerts for reactive and routine maintenance.



PC-Less Presentation

By using a USB memory stick or other storage device, you can use the projector without a computer. Menus are easy to see with a thumbnail display. Additionally there is also a slideshow and video function.



PIN Lock / MyScreen / MyText

PIN lock protection can limit projector users. MyScreen PIN lock keeps captured images on the startup screen. Users can set any name logo to MyScreen, clearly identifying ownership. MyText provides the ability to write text on the startup screen such as model name, serial number or location.



PJMessenger

PJMessenger function allows you to send and display text messages and audio alerts on your networked projectors. It is an easy and efficient way to send announcements out to multiple units.



Present Content via LAN

Hitachi's suite of networking software allows you to easily send content directly from your PC to the projector via your LAN connection.



Template Function

Line templates in the projector menu can help when writing on a whiteboard. There are four types of line templates to choose from.



Wireless Presentation Compatible

Connect the projector to a computer or your network using the optional USB wireless adapter (part number USBWL11N). The adapter supports IEEE802.11b/g and the latest 11n.



* Actual filter life will vary by individual filter and based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.

** Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

CP-AX2503 LCD Projector

Enhance the experience with Hitachi's CP-AX2503.

The CP-AX2503 ultra short throw LCD projector from Hitachi is specifically designed to enhance the visual experience — from the audience to presenters. Vivid colors. Bold graphics. Crisp text. The CP-AX2503 does it all in environments of all sizes. With 2,700 ANSI lumens of brightness and XGA 1024 x 768



resolution, the CP-AX2503 provides the perfect compatible solution. It also features a high contrast ratio, long lamp life, cloning function enabling you to copy settings data from one projector to others of the same model, and is wireless presentation ready. Plus, embedded networking gives you the ability to manage and control multiple projectors over your LAN (scheduling of events, centralized reporting, image transfer, and email alerts). Best of all, the high performance CP-AX2503 is exceptionally reliable and offers a very low cost of ownership.



3/4 View
(with cable cover)



Top View (with cable cover)




Front View (without cable cover)



Wall Mounted
(with cable cover)



Input/Outputs



- | | | |
|----------------------|--------------------------------|---|
| 1. LAN | 7. Microphone Input | 12. Video in |
| 2. USB Type A x 2 | 8. Audio in | 13. Audio in 2 |
| 3. USB Type B | 9. Audio out | 14. AC in (located on back side of the projector) |
| 4. HDMI 1 | 10. Computer in 2/ Monitor out | 15. Kensington lock |
| 5. Control (RS-232C) | 11. Computer in 1 | 16. Security bar |
| 6. HDMI 2 | | |



3LCD Technology



Closed Captioning



Crestron Integrated Partner



AMX Device Discovery



Hitachi Trade-Up Program



3 Year Warranty

HDMI HDMI

HI0259-Rev.1-04/14
All specifications subject to change without notice.
3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.
©2014 Hitachi America, Ltd. All Rights Reserved.

Hitachi America, Ltd.

Toll Free: 1.800.HITACHI • Email: dmd.info@hal.hitachi.com
Web: hitachi-america.us/projectors

CP-AX2503



Accessories	
Supplied Accessories	Remote control, power cord, computer cable, user's manual, network manual
Optional Accessories	HAS-WM03 wall mount, wall plates, wall adapter, USBWL11N USB wireless adapter, MS-1 wired and MS-1WL wireless multifunction switchers, TT-03 tabletop stand
Replacement Parts	
Lamp	DT01511 with filter
Remote Control	HL03033
Filter	UX37191

Projection Throw Chart (In inches)

Screen Size 4:3	Throw Distance	
	Diagonal	Distance from edge of projector to screen
60	4.1	15.2
70	6.7	17.8
80	9.3	20.4
90	11.9	23.0
100	14.5	25.6

Throw Ratio: (distance : width)
 0.2 : 1 from edge of projector
 0.3 : 1 from mirror cover

Specifications		
Display	Projection Technology	3LCD, 3 chip technology
	Resolution	XGA 1024 x 768
	White Light Output	2,700 ANSI lumens
	Color Light Output	2,700 ANSI lumens
	Colors	16.7 million colors
	Aspect Ratio	Native 4:3 / 16:9 and 16:10 compatible
	Contrast Ratio	5000 : 1 (using active IRIS)
Lens & Operation	Throw Ratio (distance : width)	0.2 : 1 from edge of projector to screen 0.3 : 1 from mirror cover to screen
	Focus Distance	15" - 26" from mirror cover to screen
	Display Size	60" - 100"
	Lens	F = 1.8, f = 4.21 mm
	Lamp Wattage	225W
Compatibility	Expected Lamp Life*	Approximately 3,000 hours (standard mode) 5,000 hours (Eco mode)
	Expected Filter Life**	Approximately 4,000 hours
	Speaker Output	16W x 1
	Keystone	H and V: +/- 5°
	Computer	VGA, SVGA, XGA, WXGA, WXGA+/SXGA/WSXGA+/UXGA (compressed), MAC 16"
Connectors	H-Sync	15 kHz - 106 kHz
	V-Sync	50 Hz - 120 Hz
	Composite Video	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
	Component Video	480i, 480p, 576i, 720p, 1080i, 1080p
	HDMI	480i, 480p, 576i, 720p, 1080i, 1080p, computer signal TMDS clock 27 MHz - 150 MHz
	Digital Input	HDMI x 2 (HDCP compliant)
	Computer Input 1	15-pin mini D-sub x 1
	Computer Input 2	15-pin mini D-sub x 1
	Computer Monitor Output	15-pin mini D-sub x 1 (shared with computer in 2)
	Video Input	
	S-Video	N/A
	Composite Video	RCA jack x 1
	Component Video	15-pin D-sub x 2 (shared with computer in 1/2)
	Audio Input	3.5 mm stereo mini jack x 1, RCA jack (L/R) x 1, MIC-in 3.5 mm mini jack x 1
	Audio Output	3.5 mm stereo mini jack x 1
Network LAN Wired	RJ-45 port (10 base-T / 100 base-TX)	
Network LAN Wireless	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	
USB	Type A x 2 (PC-less presentation, wireless adapter) Type B x 1 (USB display or mouse control)	
Control Terminals	9-pin D-sub x 1 (RS-232 control)	
Ratings & Warranty	Power Supply	AC100-120V / AC220-240V, 50/60Hz
	Power Consumption	330W
	Operating Temperature	32°F - 104°F (0°C - 40°C)
	Dimensions (W x D x H)	14.8" x 14.2" x 5.4" (excluding protruding parts)
	Weight	Approximately 9.5 lbs
	Approvals	UL 60950-1 / cUL, FCC part 15 subpart B Class B
Warranty	3 year limited parts and labor Extended Service Contract available (additional cost)	



* Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

** Actual filter life will vary by individual filter and based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.

CP-AX2503

