

Better meetings with IAdea signboard



PoE



Touch



Zero Gap



Tempered Glass



Light Bar



NFC Option



One-Wire Installation



Flush Mount



Elegant Product Design



Instant On-site Booking

XDS-1078 Smart Signboard




Authenticating access request

Enhances room management efficiency with touch-enabled authentication of IDs.



Brandable with LED lightbar

Thousands of colors to choose from to signal room status and showcase corporate identity.



Learn more about our software partners here



1-wire Installation

Easy installation with PoE (Power over Ethernet), which transmits power and information

Instant on-site booking

Increases operation efficiency by eliminating time-consuming typing and submitting via website, but instead, allowing meetings to be booked directly from the panel in-person.

Product Photos

Flush mount + VESA mount + Glass mount

Unlike most typical signboards, XDS-1078 is flush mounted and much closer to the wall to deliver a much more visually pleasing and user intuitive industrial design of the system. IAdea provides step by step mounting guide, as easy as 1, 2, 3.



VESA mount



Flush mount



Glass mount

Technical Specification

Open Standards Supported

- HTML5, JavaScript, and CSS
- Android 4.4 API
- W3C SMIL for cross-platform management
- W3C Widgets for HTML delivery
- POPAI Digital Signage Content Standards, including:
 - S1 (JPEG 480p baseline)
 - S2 (JPEG 720p baseline)
 - S4 (MPEG L2 audio)
 - S5 (MP3 audio, 384Kbps)
 - S6 (MPEG-1 SIF, 3Mbps CBR)
 - S7 (MPEG-1 480p, 10Mbps CBR)
 - S8 (MPEG-1 720p, 15Mbps CBR)
 - S9 (MPEG-2 480p, 6Mbps CBR)
 - S10 (MPEG-2 720p, 12Mbps CBR)
 - S11 (H.264/MPEG-4 AVC, 480p, 6Mbps CBR)
 - S12 (H.264/MPEG-4 AVC, 720p, 10Mbps CBR)
- E1 (PNG 24bpp+alpha, 480p)
- E2 (PNG 24bpp+alpha, 720p)
- E4 (VC-1/WMV9, MP@ML, 720p)
- E7 (MPEG-4 ASP, 480p, 10Mbps CBR)
- E8 (H.264/MPEG-4 AVC, 1080p, 20Mbps CBR)

Advanced Signage Features

- Remote commissioning
- AlwaysOn, AppLock to prevent unauthorized access
- StrongCache for continued playback even when network is not available

HTML5 Support

- Widgets for calendar, clock, news, weather, Twitter, and web page integration
- HTML5 technologies including CSS and Javascript
- WebKit-based browser engine, same as Google Chrome™ and Apple Safari® browsers

Display and Sound

- 10.1" LCD wide aspect ratio
- 10 points multi-touch
- 300 nits maximum brightness
- 1280x800 high resolution
- View Angle: 170 x170
- Built-in stereo speakers 1W x2
- Programmable LED bar x 2
- HDMI output to external display

Content Management

- SignApps Express Utility
- 3rd party solution (optional license)

Connectivity

- Wi-Fi:802.11 b/g/n
- Multi-points touch
- Ethernet 10/100 BASE-T
- 3.5mm analog stereo audio out
- USB 2.0 x 2
- Micro USB for ADB
- Optional 3G/4G mobile module via USB
- External NFC module (optional)

Local Storage

- 8 GB eMMC memory (approx. 360 minutes of typical 720p video @3 Mbps)
- Micro SD card slot (support up to 32GB storage)

Mounting Kit

- Built-in VESA compatible 75x75(mm) posts
- Flush mount back cover and glass mount (optional)

Supplied Accessories

- Table stand
- Adapter
- Power plug
- DC in & Micro SD stopper
- HW & SW QSG

Expansion Options

- 16GB/32GB micro SD/SDHC memory card

AC Adapter

- Input: 100-240V, 50-60 Hz, 0.5A Max.
- Output: 12V, 1.5A
- UL/CB certified power supplies
- Interchangeable connector system includes US plugs (Option for EU, UK and AUS plugs)
- Power-over-Ethernet (PoE) single-wire installation

Environmental

- Operating temperature: 0 to 40°C
- Storage Humidity: 10 to 85% @ 40°C, non-condensing

Dimensions for Product & Package

- Size:
 - 269.88mm(W)x 170.77mm (H)x 28.5 mm (D)
 - 10.62" (W) x 6.72" (H) x 1.12"(D)
- Weight: 727g/1.6 lb
- Individual Package Size:
 - 336mm (W) x 100mm(H) x 227 mm (D)
 - 13.2"(W) x 3.93"(H) x 8.93 (D)
- Outer Carton Size:
 - 695mm (W) x 260mm (H) x 530 mm(D)
 - 27.36"(W) x 10.23"(H) x 20.86"(D)
- Units per Outer Carton: 10

Certifications

- CE/FCC

Warranty

- 1-year limited parts & labor

IAdea Headquarter

3F, No. 21, Lane 168, Xingshan Road
Taipei, Taiwan 114
Phone: +886-2-2791-1110
Fax: +886-2-2791-1170
Email: Sales@IAdea.com

IAdea America Corp.

20 Fairbanks, Suite 170
Irvine, CA 92618
Tel: +1-949-305-6489
Email: US-Sales@IAdea.com

