

IN CEILING SPEAKER

6.5" 2-WAY, 8 OHMS

ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA



GENERAL SPECIFICATIONS

MODEL NUMBER:	IC6TBBC (UL Listed)
DESCRIPTION:	6.5" 2-Way Co-Axial Speaker w/ Tile Bridge and Backcan
COVERED OUTDOOR:	Yes
IMPEDANCE:	8 ohms
SENSITIVITY (1W/1M):	86.5 dB
DISPERSION:	140°
MAX POWER:	50 watts
NOMINAL POWER:	25 watts
FREQUENCY RESPONSE:	45 Hz - 20 kHz
CROSSOVER:	4 kHz
WOOFER SIZE:	6.5"
WOOFER MATERIAL:	Paper Coated Polyurethane Surround
TWEETER SIZE:	0.5" (13mm) balance tweeter
TWEETER MATERIAL:	Hard Dome (Ferrofluid Cooled)
GRILL MATERIAL:	Aluminum
GIFT BOX DIMENSIONS (LxWxH):	21" x 10" x 5"
GIFT BOX WEIGHT:	6.30 lbs.
MASTER CARTON DIMENSIONS (LxWxH):	22" x 21" x 18"
MASTER CARTON QUANTITY:	6 pairs
CUT OUT SIZE:	7 5/8" (194mm)
WEIGHT:	2.90 lbs.
MOUNTING HARDWARE:	4 each Mounting Clamps 1 each Tile Bridge (6TB) 1 each Backcan
PAINTABLE:	Yes



Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com