

IN CEILING SPEAKER

6.5" 2-WAY, 8 OHMS

ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA

GENERAL SPECIFICATIONS



MODEL NUMBER: ICT62A	
DESCRIPTION:	6.5" 2- Way Co-Axial Swivel Tweeter
COVERED OUTDOOR:	Yes
IMPEDANCE:	8 Ohms
SENSITIVITY (1W/1M):	88 dB
DISPERSION:	120°
MAX POWER:	150 Watts
NOMINAL POWER:	100 Watts
FREQUENCY RESPONSE:	50 Hz - 20 kHz
CROSSOVER:	4 kHz
HIGH FREQUENCY DRIVER:	1" (25 mm) Swivel Soft Dome
LOW FREQUENCY DRIVER:	6.5"(165 mm) Aluminum/Rubber
WOOFER SIZE:	6.5"
WOOFER MATERIAL:	Aluminum/Rubber
TWEETER SIZE:	1" Swivel Soft Dome
TWEETER MATERIAL:	Ceramic
TWEETER PROTECTION FUSE:	Yes
TWEETER CONTROLS:	+/- 3 dB Switch
GRILL MATERIAL:	Aluminum
DEPTH:	2 15/16 "(7mm)
OVERALL SIZE:	9"(228mm)
GIFT BOX DIMENSIONS (LxWxH):	11" x 11" x 11"
GIFT BOX WEIGHT:	7.35 lbs.
MASTER CARTON DIMENSIONS (LxWxH):	23" x 22" x 13"
MASTER CARTON QUANTITY:	4 pairs
CUT OUT SIZE:	7 5/8" (194 mm)
WEIGHT:	4.25 lbs.
MOUNTING HARDWARE:	Kwik Klamps
PAINTABLE:	Yes



Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com