

VOLTAGE/CONTINUITY TESTERS

MEASURE/INDICATE AC/DC VOLTAGE

- Two new Voltage/Continuity Testers for 2021
- cULus Listed (all models)
- CAT IV 600V & CAT III 600V options
- Digital Multifunction, Analog and Solenoid Models
- IP42 Dustproof/Water (61-557 & 61-547)
- 2 Meter drop protection (61-557 & 61-547)
- Lead holders are spaced to test tamper resistant outlets
- Bright LED flashlight, continuity, NCVT, GFCI test, LoZ (61-557)



61-557

Voltage & Continuity Tester
w/LCD, GFCI, Flashlight & NCVT
CAT IV 600V



61-076

Voltage & Continuity Tester
5-600V
CAT III 600V



61-547

8 Range AC/DC Voltage Indicator
w/Polarity Indicator
CAT III 600V



61-065

Voltage Tester
5-600V
CAT III 600V



NCV — Flashlight



NCV, Continuity,
High Voltage,
Visual Indications,
Augment Audible
Indications

LoZ
Eliminates ghost
voltage
(induced voltage
from adjacent
conductors)

Uses Standard
Test Leads
(included)





Probe Holder
for Storage/
Measurement
(61-557, 61-547)



Universal Magnetic
Strap Clip
(61-557, 61-547)

Universal Magnetic
Strap Clip
(UMHS-757)
allows for two-handed
operation of probes with
tester suspended from
strap (61-557 & 61-547)
(sold separately)

VOLTAGE/CONTINUITY TESTERS AND VOLTAGE TESTERS


VOLTAGE TESTER SELECTION GUIDE FOUR NEW NCVTS FOR 2021	 NEW	 NEW		
	61-557	61-547	61-076	61-065
FEATURES				
CAT Rating (Safety)	CAT IV 600V	CAT III 600V	CAT III 600V	CAT III 600V
Listing Preferred	cULus, CE	cULus, CE	cULus	cULus
Drop Protection	6.6 ft. (2m)	6.6 ft. (2m)		
Ingress Protection	IP42	IP42	—	—
AC Voltage (Volts)	6 ~ 600	24 ~ 600	5 ~ 600	100 ~ 600
DC Voltage (Volts)	6 ~ 600	12 ~ 600	5 ~ 600	100 ~ 600
High Voltage Alarm	ACV >36 or DCV >50V	ACV/DCV >48V	—	—
Audible Continuity	✓	—	—	—
Visual Continuity	✓	—	✓	—
Backlight	✓	—	—	—
Low Impedance (LoZ)	✓	—	✓	✓
NCV	90-600V AC	—	—	—
Auto Ranging	✓	—	—	—
Magnetic Strap Mount	✓	✓	—	—
Test Probe Holder	✓	✓	✓	✓
Flashlight	✓	—	—	—
Auto-Power Off (APO)	✓	—	—	—
Low Battery Indicator	✓	—	—	—
Battery Type (included)	3 x 1.5V AAA	—	4 x 1.5V LR44	—
LCD Display Count	600	—	—	—
Backlight	✓	—	—	—
DC Polarity Indication	✓	✓	✓	—
Leads	Removable	Fixed	Removable	Removable
GFCI Test	✓	—	—	—
Display	LCD	Neon Lamps	Indicator Movement	Indicator Movement
Warranty	2-Year*	2-Year*	2-Year*	2-Year*
ACCESSORIES				
Test Leads (included)	TL-757	—	61-070	61-070
Magnetic Hanging Strap (sold separately)	UMHS-757	UMHS-757	—	—




Scan this QR code with your smartphone to learn more about the testers.



Probe Holders are spaced to test tamper resistant outlets (61-557 & 61-547)



Continuity Testing (61-557 & 61-076)



Backlit Display and Flashlight (61-557)



NCVT in tip detects presence of AC voltage (61-557)



Tests GFCI protected circuits (61-557)



LoZ option to eliminate ghost voltage (61-557)



IDEAL INDUSTRIES, INC.

IDEAL INDUSTRIES, INC.
1800 S. Prairie Drive, Sycamore, IL 60178, USA / 815-895-5181 • 800-435-0705 in USA

International offices:
Australia • Canada • China • France • India • Germany • Mexico • UK

For complete sales office contact information, visit us at:
www.idealind.com