






The New Way to Collaborate

Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Large touchscreen displays to engage your audience and fit your budget

The InFocus JTouch™ combines precise touchscreen technology with a bright, colorful LCD display to engage audiences in classrooms and beyond.

- 55-inch, 65-inch or 70-inch 1080p touch display for a great price
- Add touch to your system's Windows apps, even the older ones
- Your content will be interactive, bright and crisp in any light
- Accurate and responsive touch overlay with multi-touch capability
- Multiple ways to quickly connect and display your notebook



Brightness and Clarity

JTouch helps you get your message across and connect with your audience with incredible brightness, color and clarity. Your images, text and video will be seen and enjoyed even in large spaces with high ambient light.

Engage Your Audience with Touch

Whether you're in a classroom, board room or at a trade show, the interactivity of JTouch engages audiences and encourages participation. JTouch gets students involved, attracts customers, and provides a great medium for testing and presenting touch-enabled applications.

Easy to Connect

JTouch provides multiple ways to display your content, including HDMI, VGA, component video, and wireless via optional InFocus LiteShow adapter. To enable touch, simply connect the JTouch to your PC via USB. No software install needed.

Multi-touch with Gestures

Use multi-point touch gestures to manipulate your content and traverse your Windows PC on the giant touchscreen. Your software and content will come to life on a giant scale to engage your audience and encourage their interaction.

Location, Location

Secure the JTouch to the wall with its standard VESA mounting pattern or mount it on an optional InFocus mobile cart. A mobile cart lets you position it in multiple locations within a room or share it between multiple rooms — wherever it's needed most.



Specifications*

Display	INF5520A-NOPC	INF6501A	INF7001	
Size	55" diagonal	65" diagonal	70" diagonal	
Resolution		1920 × 1080		
Refresh Rate	60 Hz	120 Hz	200 Hz	
Viewing Angle	±188° ±176°			
Technology	CCFL LCD	W-LED LCD	E-LED LCD	
Pixel Pitch	0.63mm			
Picture-in-Picture	SBS/4 quadrant PiP	N/A		
Computer Compatibility	Display: PC, Mac			
	Touch: PC (Windows gestures), Mac (single point touch only)			
Input Connections	HDMI × 2, VGA (HD15 VESA), Component,	HDMI, DVI, VGA (HD15 VESA), USB Type A x	HDMI x 2, HDMI (ARC) x 1, VGA (HD15 VESA), USI	
	S-Video, Composite, RS232, RCA stereo audio	4, 3.5mm stereo audio in, USB Type-B for	Type A x 2, SPDIF Optical, Component, RCA stere	
	× 2, 3.5 mm stereo audio in, USB Type-B	touch screen control (USB cable included)	audio (L/R) in, 3.5mm stereo audio in, LAN, USI	
	for touch screen control		Type-A cable for touch screen control	
Output Connections	RCA audio stereo (L/R) output	3.5mm stereo audio out	3.5mm stereo audio out	
Touch Screen	Edge-to-edge multi-touch system with support for Windows 7/8 gestures (PC only).			
	Glass protection overlay for LCD surface. USB cable from touch system panel board to PC.			
Touch Points	5-point	2-point	4-point	
Speakers (Integrated)	Stereo 7W × 2 Stereo 10W x 2			
Power	AC 100 to 240V, 50/60Hz			
Mount	VESA standard 400 × 400mm M6 screws			
System				
Accessories Included	Table stand assembly (in separate box),	Power cord, VGA cable, USB Type-A to Type-B	Power cord, remote control, user guide	
	power cord, remote control, user guide	cable, remote control, user guide		
Warranty	1 Year			
Product Weight	122.4 lbs / 55.5 kg	110.2 lbs / 50 kg	121.3 lbs / 55 kg	
Product Dimensions	53 x 5.5 x 32.3 in / 1346 x 140 x 820 mm	60.2 x 3.3 x 36.4 in / 1529 x 85 x 924 mm	64.3 x 3.7 x 38.8 in / 1632 x 94 x 986 mm	
Shipping Weight	135 lbs / 61.2 kg	150 lbs / 68 kg	154 lbs / 69.8 kg	
Shipping Dimensions	58.7 x 14 x 38.4 in / 1490 x 352 x 975 mm	68 x 9.5 x 40 in / 1727 x 241 x 1016 mm	70.6 x 9.5 x 43.7 in / 1792 x 240 x 1110 mm	
	41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m	32 to 104°F at 0 to 10K ft / 0 to 40°C at 0 to 3,048 m	41 to 95°F at 0 to 10K ft/5 to 35°C at 0 to 3,048 m	
Operating Conditions	12 10 75 7 41 0 10 2011 11/ 5 10 55 0 41 0 10 5,0 10 11	<40dBA @ 77° F / 25°C		
Operating Conditions Noise			,	

Accessories

(INF-VIDSHELF)

BigNote Whiteboard Software (INS-BIGNOTE)

Wall Mount (INF-WALLMNT2)

Floor Stand for INF5520A-NOPC only (INF-FLRSTND)

Mobile Cart for INF5520A-NOPC only (INF-MOBCART)

Accessories Shelf for INF-MOBCART or INF-FLRSTND (INF-ACCYSHELF)

Webcam Shelf for INF-MOBCART or INF-FLRSTND

Pro Mobile Cart in Black (INF-MOBCARTPRO-B)

Pro Mobile Cart in Silver (INF-MOBCARTPRO-S)

Accessories Shelf for Pro Mobile Cart in Black

(INF-ACCYSHELFPRO-B)

Accessories Shelf for Pro Mobile Cart in Silver

(INF-ACCYSHELFPRO-S)

LiteShow Wireless Adapter (INLITESHOW3)

USB to HDMI Adapter (HW-USB2HDMI)

Extended warranties

©2014 InFocus Corporation. All rights reserved. Specifications are subject to change without further notice. InFocus, InFocus The New Way to Collaborate and JTouch are either trademarks or registered trademarks of InFocus Corporation in the United States and other countries. All trademarks are used with permission or are for identification purposes only and are the property of their respective companies. InFocus-JTouch-2page-Datasheet-EN-28FEB14.



INF7001 back panel





205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

 $[\]mbox{\ensuremath{^{\star}}}$ Product specifications, terms, and offerings are subject to change at any time without notice.