INF5533e

Customizable, open Android platform, 55-inch display for K-12

Part #: INF5533e

InFocus

With 4K resolution, Total Touch Control[™], built-in education features, and the ability to natively run Android apps, the JTouch Plus INF5533e is a fully customizable, all-in-one teaching, collaboration, and presentation solution - the most education-friendly JTouch ever.

Key Features

- Navigate a friendly, easy-for-anyone interface with Total
 Touch Control™ no need for a remote
- Built-in whiteboard, browser, file explorer, as well as AirPlay and EShare for wireless casting
- Annotate over any application or video input
- Comment and draw over websites, documents, and more
- Brilliant 55-inch, 4K resolution screen with anti-glare
- Add any Android app
- Customize your whiteboard background



Open Android Platform

Expand and customize your platform with any Android application or game. Simply download and install as you would on your phone.

Four Critical Applications

All JTouch Plus models include the four critical applications needed for interactive touch panels: Casting, Whiteboarding, Browsing, and File Viewing. Create on a full-featured digital whiteboard, present videos and photos, browse the web, easily connect and share content from your Apple, Windows, or Android devices with wireless casting.

Intuitive Touch

Erase, zoom, and pull up menu options quickly and easily with incredibly intuitive touch gestures on the JTouch Plus. Use one finger to draw, two fingers to move, and three fingers to erase on the whiteboard or when annotating on any screen. A simple swipe gesture on either side of the screen reveals a full menu of further options.

Interactive whiteboard

Draw, write, and capture notes on a fully customizable, built-in digital whiteboard. Choose any background on a multi-screen canvas with room for free-form drawings, diagrams, and more. Draw using your finger or one of the provided styli using a complete collection of digital pens, highlighters, shapes, lines, and colors.

Multi-input Touch Monitor

Plug up to eight devices into your INF5533e monitor. HDMI-based sources can also connect via five separate USB-B ports to access the panel's touch control. Front access IO ports make it convenient to connect, view, and touch control any user's PC temporarily with both HDMI and Touch USB.

Optional PC

Turn your INF5533e into a fully integrated, powerful all-in-one Windows 10 PC with touch by adding the optional Core i5 OPS PC Module (coming soon).

Specifications*

Diagonal Size 5°5 Resolution — Native 4K UHD (3840 x 2160) Display Technology Direct-LED backlight Touch Screen Features Antiglane, Anti-Fingerprint, 10-point IR touch Glass Strength 4mm thick, heat treated Contrast Ratio 1 200-1 Contrast Ratio 120-01 Display Brightness 350 cd/m2 Response Time 8.0 ms Pixel Pitch 0.429 mm Viewing Angle 176° Speakers Sterce 10W x 2 Speakers Ses232, Component video, Composite video, HDMI x 4, RJ 45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio in [testree, VGA Audio source), VB' Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RA L/R audio Display Connectors – Outputs R5232, 35mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Power Standard AC 100 to 240V, 50/60 PC Hardware OPS Bay System Procentions System Procential Conditions Casting embedded Audible Noise 4 0 dBA at 77F / 25°C Operating Conditions 2 to 104°F at 0 to 100000 ft / to 100000 ft / to 104°C at 0 to 3048 m/ to 100	Display	INF5533e
Display Technology Direct-LED backlight Touch Screen Features Anti-glare, Anti-Fingerprint, 10-point IR touch Class Strength 4mm thick, heat treated Scratch Resistance 7 Mohs Contrast Ratio 1,2001 Display Brightness 350 cd/m2 Refresh Rate 100 Hz Response Time 0,429 mm Viewing Angle 176* Speakers Stereo 10W x 2 Speakers Stereo 10W x 2 Display Connectors – Inputs RS232, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x 2, Media USB (Android), PC Audio in (stereo, VGA Audio source), VG* Microphone (Mono linked to 0PS), USB 2.0 x 2, 0PS PC USB x 2, CK A. R audio Display Connectors – Outputs RS232, Smm Pc audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x 2 (for touch control), RCA L/R audio PC Hardware 0 PS By PC Hardware 0 PS By System Stream System Stream System Stream System Stream System Stream System Stream Operating Conditions 32 to 104 ff at 0 to 100000 ft	Diagonal Size	55"
Touch Screen Features Anti-glare, Anti-Fingerprint, 10-point IR touch Glass Strength 4mm thick, heat treated Scratch Resistance 7 Mohs Contrast Ratio 1,200-1 Display Brightness 350 cd/m2 Refresh Rate 120 Hz Response Time 8.0 ms Pixel Pitch 0,429 mm Viewing Angle 176° Speakers Stereo 10W x 2 RS232, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8° Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA UR audio Display Connectors – Outputs RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Pover Standard 0 100 to 240V, 50/60 PC Hardware PC Hardware OPS Bay System Vireless Collaboration Casting embedded Audible Noise < 40 dBA at 77F / 25°C	Resolution – Native	4K UHD (3840 x 2160)
Glass Strength 4mm thick, heat treated Scratch Resistance 7 Mohs Contrast Ratio 1,200:1 Display Prightness 350 cd/m2 Refresh Rate 120 Hz Response Time 8.0 ms Pixel Pitch 0.429 mm Viewing Angle 176° Speakers Stereo 10W x 2 RS292, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PCA L/R audio Display Connectors – Outputs RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Power Standard RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Power Standard OPS Bay System VEA PC Hardware OPS Bay System System Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77F / 25°C	Display Technology	Direct-LED backlight
Scratch Resistance 7 Mohs Contrast Ratio 1,200-1 Display Brightness 350 cd/m2 Refresh Rate 120 Hz Response Time 8.0 ms Pixel Pitch 0.429 mm Viewing Angle 176° Speakers Stereo 10W x 2 RS232, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio in (stereo, VGA Audio source), 1/8° Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, 35mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Power Standard RS232, 35mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio PC PC PC PC PC PC PC Power Standard OPS Bay System Power Cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77°F / 25°C Operating Conditions 32 to 104°F at 0 to 100000 ft / 0 condoction of condoction	Touch Screen Features	Anti-glare, Anti-Fingerprint, 10-point IR touch
Contrast Ratio 1,200:1 Display Brightness 350 cd/m2 Refresh Rate 120 Hz Response Time 8.0 ms Pixel Pitch 0.429 mm Viewing Angle 176' Speakers Stereo 10W x 2 RS232, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC, Audio in (stereo, VGA Audio source), 1/8' Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Power Standard AC 100 to 240V, 50/60 PC Hardware OPS By System Uncluded Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Qualible Noise 4.0 dBA at 77F / 25'C Operating Conditions 32 to 104'F at 0 to 10000 ft / 0 to 40'C at 0 to 304B m Mounting Pattern VESA 400-600mm with M8 screws Product Dimensions 30.8 x 50.8 x 42 in / 782.3 x 1290.3 x 106.7 mm Product Weight 84 lbs / 38.1 kg Shipping Dimensions 38 x 59.	Glass Strength	4mm thick, heat treated
Display Brightness 350 cd/m2 Refresh Rate 120 Hz Response Time 8.0 ms Pixel Pitch 0.429 mm Viewing Angle 176° Speakers Stereo 10W x 2 Bas 232, Component video, Composite video, HDMI x 4, R)-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), I/8° Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Power Standard AC 100 to 240V, 50/60 PC PC PC POWER Post Bard Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise 4 0 dBA at 77F / 25°C Operating Conditions 32 to 104F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m Mounting Pattern VESA 400×600mm with M8 screws Product Warranty 2 years Product Weight 84 lbs / 38.1 kg Shipping Dimensions 85 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Scratch Resistance	7 Mohs
Refresh Rate 120 Hz Response Time 8.0 ms Pixel Pitch 0.429 mm Viewing Angle 176* Speakers Stereo 10W x 2 Display Connectors – Inputs RS232, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), V8* Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Power Standard AC 100 to 240V, 50/60 PC PC PC Hardware OPS Bay System System Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77°F / 25°C	Contrast Ratio	1,200:1
Response Time 8.0 ms Pixel Pitch 0.429 mm Viewing Angle 176° Speakers Stereo 10W x 2 Bread In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, Component video, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Display Connectors – Outputs RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Display Connectors – Outputs RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Power Standard AC 100 to 240V, 50/60 PC PC PC PC PC PC Hardware OPS Bay System Inclued Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise 40 dBA at 77°F / 25°C Operating Conditions 32 to 104°F at 0 to 100000 ft / 0 to 40°C at 0 to 3048 m Mounting Pattern VESA 400×600mm with M8 screws Product Warranty 2 years Product Dimensions 30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mm Product Weight 84 lbs / 38.1 kg Shipping Dimensions 38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Display Brightness	350 cd/m2
Pixel Pitch 0.429 mm Viewing Angle 176° Speakers Stereo IOW x 2 By Seasy (Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio in (stereo, VGA Audio source), 1/8° Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS.232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Power Standard AC 100 to 240V, 50/60 PC PC PC Hardware OPS Bay System System Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 777F / 25°C	Refresh Rate	120 Hz
Viewing Angle 176° Speakers Stereo 10W x 2 Display Connectors – Inputs RS232, Component video, Composite video, HDM1 x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Power Standard AC 100 to 240V, 50/60 PC Hardware OPS Bay System Vireless Collaboration Casting embedded Micelas Collaboration Casting embedded Audible Noise < 40 dBA at 77°F / 25°C	Response Time	8.0 ms
Speakers Stereo 10W x 2 RS232, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Power Standard AC 100 to 240V, 50/60 PC PC Hardware OPS Bay System Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise 40 dBA at 77"F / 25"C Operating Conditions 32 to 104"F at 0 to 10000 ft / 0 to 40"C at 0 to 30048 m Mounting Pattern VESA 400×600mm with M8 screws Product Warranty 2 years Product Dimensions 30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mm Product Weight 84 lbs / 38.1 kg Shipping Dimensions 38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Pixel Pitch	0.429 mm
RS232, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Power Standard AC 100 to 240V, 50/60 PC PC Hardware OPS Bay System Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise 40 dBA at 77F / 25°C Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m Mounting Pattern VESA 400×600mm with M8 screws Product Warranty 2 years Product Uimensions 30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mm Product Weight 84 lbs / 38.1 kg Shipping Dimensions 38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Viewing Angle	176°
Display Connectors – Inputs PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio Power Standard AC 100 to 240V, 50/60 PC PC PC PC Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise 4 do BA at 77"F / 25"C Operating Conditions 32 to 104"F at 0 to 100000 ft / 0 to 40"C at 0 to 3048 m Mounting Pattern VESA 400×600mm with M8 screws Product Warranty 2 years Product Dimensions 30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mm Product Weight Shipping Dimensions 38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Speakers	Stereo 10W x 2
Power Standard PC	Display Connectors – Inputs	PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2,
PC PC Hardware OPS Bay System Included Accessories Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77° F / 25°C	Display Connectors – Outputs	RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio
PC HardwareOPS BaySystemIncluded AccessoriesPower cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi AdapterWireless CollaborationCasting embeddedAudible Noise< 40 dBA at 77°F / 25°COperating Conditions32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 mMounting PatternVESA 400×600mm with M8 screwsProduct Warranty2 yearsProduct Dimensions30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mmProduct Weight84 lbs / 38.1 kgShipping Dimensions38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Power Standard	AC 100 to 240V, 50/60
Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77°F / 25°C Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m Mounting Pattern VESA 400×600mm with M8 screws Product Warranty 2 years Product Dimensions 30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mm Product Weight 84 lbs / 38.1 kg Shipping Dimensions 38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	PC	
Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77°F / 25°C Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m Mounting Pattern VESA 400×600mm with M8 screws Product Warranty 2 years Product Dimensions 30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mm Product Weight 84 lbs / 38.1 kg Shipping Dimensions 38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	PC Hardware	OPS Bay
Wireless CollaborationCasting embeddedAudible Noise< 40 dBA at 77°F / 25°C	System	
Audible Noise $<40 \text{ dBA at } 77^{\circ}\text{F}/25^{\circ}\text{C}$ Operating Conditions $32 \text{ to } 104^{\circ}\text{F at } 0 \text{ to } 10000 \text{ ft } / 0 \text{ to } 40^{\circ}\text{C at } 0 \text{ to } 3048 \text{ m}$ Mounting PatternVESA $400 \times 600 \text{ mm}$ with M8 screwsProduct Warranty 2 years Product Dimensions $30.8 \times 50.8 \times 4.2 \text{ in } / 782.3 \times 1290.3 \times 106.7 \text{ mm}$ Product Weight $84 \text{ lbs } / 38.1 \text{ kg}$ Shipping Dimensions $38 \times 59.8 \times 9.6 \text{ in } / 965.2 \times 1518.9 \times 243.8 \text{ mm}$	Included Accessories	Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter
Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m Mounting Pattern VESA 400×600mm with M8 screws Product Warranty 2 years Product Dimensions 30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mm Product Weight 84 lbs / 38.1 kg Shipping Dimensions 38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Wireless Collaboration	Casting embedded
Operating Conditions0 to 40° C at 0 to 3048 m Mounting PatternVESA $400 \times 600 \text{mm}$ with M8 screwsProduct Warranty2 yearsProduct Dimensions $30.8 \times 50.8 \times 4.2 \text{ in /}$ $782.3 \times 1290.3 \times 106.7 \text{ mm}$ Product Weight $84 \text{ lbs / } 38.1 \text{ kg}$ Shipping Dimensions $38 \times 59.8 \times 9.6 \text{ in /}$ $965.2 \times 1518.9 \times 243.8 \text{ mm}$	Audible Noise	< 40 dBA at 77°F / 25°C
Product Warranty2 yearsProduct Dimensions30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mmProduct Weight84 lbs / 38.1 kgShipping Dimensions38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Operating Conditions	· · · · · · · · · · · · · · · · · · ·
Product Dimensions 30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mm Product Weight 84 lbs / 38.1 kg Shipping Dimensions 38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Mounting Pattern	VESA 400×600mm with M8 screws
Product Dimensions 782.3 x 1290.3 x 106.7 mm Product Weight 84 lbs / 38.1 kg Shipping Dimensions 38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Product Warranty	2 years
38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Product Dimensions	,
Shipping Dimensions 965.2 x 1518.9 x 243.8 mm	Product Weight	84 lbs / 38.1 kg
Shipping Weight 104 lbs / 47.2 kg	Shipping Dimensions	
	Shipping Weight	104 lbs / 47.2 kg

 $^{^{\}star}$ Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

1 Year Extended Warranty for Select 55-inch Touchscreens (EPW-55JT1)

Mobile Cart Pro for up to 75-inch Displays (Black) (INF-MOBCARTPRO-B)

SimpleShare Presentation System (INA-SIMPS1)

SimpleShare (INA-SIMS1)

SimpleShare Touch Presentation System (INA-SIMINT1)

LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)

Wall Mount for up to 75-inch Display (INF-WALLMNT2)

Floor Stand for up to 75-inch Displays (INF-FLRSTND)

Mobile Cart for up to 75-inch Displays (INF-MOBCART)

Mobile Cart for Vertical Lift Mount (INA-CARTBB)

Vertical Lift Display Wall Mount (INA-MNTBB70)

VESA Interface Bracket for Vertical Lift Mounts (INA-VESABB)

Floor Support for Lift Wall Mount (INA-SUPPORTBB)

Lift Case for 55-inch to 65-inch Displays (CA-ATALIFT65)

Remote Control for Mondopad, BigTouch or JTouch (INA-REMOTE2)

Mini USB WiFi Adapter (INA-WIFIUSB-3)

Qwizdom Software Bundle (INS-QBUNDLE)

Oktopus Blend Software (INS-QBLEND1T40-1Y)

Ximbus Software (INS-QXIM1T40-1Y)

InFocus Whiteboard App for Android (INS-AND-WHIT)

InFocus Browser App for Android (INS-AND-BROW)

InFocus FileViewer App for Android (INS-AND-FILE)

2 Year Extended Warranty for Select 55-inch Touchscreens (EPW-55JT2)

3 Year Extended Warranty for Select 55-inch Touchscreens (EPW-55JT3)