

205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com



JTouch Interactive Displays

Touchscreens that enhance collaboration & captivate audiences



JTouch Interactive Displays

Whether you're in a classroom or huddle space, a conference room or auditorium, there's a JTouch interactive display solution to fit your needs and engage your audience.





Full Touch Control

Display your PC, Mac, or Chromebook via HDMI or VGA & control it from the display via touch using a USB cable.

- Extend the reach of your computer's USB ports with easilyaccessible USB ports on the display
- No calibration or special stylus means it's quick and easy to use with just your fingertips

High Brightness and HD Clarity

JTouch helps you get your message across and connect with your audience with incredible brightness, color and clarity. With 1080p and 4K resolution, your images, text and video will be seen and enjoyed even in large spaces with high ambient light.

Key Features

- Giant, high resolution touch display for a great price
- Incredibly sharp 4K resolution on 70 -, 75-, and 85-inch models
- 40-, 57-, and 65-inch models offer bright, vivid 1080p HD resolution
- Run all your apps, even the older ones, with touch
- Accurate and responsive touch overlay with multi-touch capability

Casting

Add the LightCast Key to your JTouch to easily connect and share content from nearly any computer or mobile device. You'll make meetings, lessons and teamwork more efficient, engaging and easy.

LightCast technology works seamlessly with all your device's native protocols – use AirPlay (Mirroring mode) for Apple, and Miracast for Android or Windows.**

Use the InFocus LightCast Sender to cast using Chrome extension (works on Apple, Windows, or Chrome OS.)

Browse the Web

Access your favorite online content without a connected computer.

View Documents

View and present Office files, as well as most photo and video file formats, directly from the JTouch.

Create on an Interactive Whiteboard

Capture ideas on a giant, multi-screen canvas.

LightCast is included in select JTouch models, or unlock the power of wireless with a LightCast Key. Visit InFocus.com or contact your reseller for more information.

Interactive Whiteboard and Annotation

Stop taking photos of your old dry-erase board & step up to a digital whiteboard. You'll never lose an idea & your meetings will be more efficient & productive.

Draw, Write, & Capture Notes

- Create a whiteboard on a multi-screen canvas, with room for free-form drawings, diagrams, images, and notes
- Write or draw with complete collection of digital pens, highlighters, shapes, lines and colors
- Use with fingers or a stylus
- View and annotate over PowerPoint, images, Word and more.
- Save and share your notes electronically

Built into INF4030/p, INF6502WB/p, INF6502WBAG/p, INF7002e, INF7002WB, INF7002WBAG, and INF7530eAG /INF7530AG



The most education-friendly JTouch ever

JTouch Plus INF7530eAG

The totally customizable INF7530eAG features 4K resolution, Total Touch Control[™], and the ability to natively run Android applications.

- Navigate a friendly, easy-for-anyone interface with Total Touch Control[™] no need for a remote
- Built-in whiteboard, browser, media player, and AirPlay capability
- Annotate over any application or video input
- · Comment and draw over websites, documents, and more
- Brilliant 75-inch, 4K resolution screen with anti-glare
- Add Android apps
- Customize your whiteboard background
- Erase with three-finger touch



"Overall the JTouch is a jack of all interactive trades – it has the ability to draw in a rainbow of colors, display smooth video and let you connect without needing a new app."

-Brian Nadel, Computerworld

Choose Your JTouch

| | 40-inch | 57-inch | 65-inch | 70-inch | 75-inch | 85-inch | |
|-----------------------|-----------------------|-----------------------------|---|-----------------------|----------|----------------------------|--|
| Wireless | With LightCast Key | Optional with LiteShow 4 | INF6502WB and INF6505 series with LightCast Key | With LightCast Key | - | | |
| Digital Whiteboard | 1 | With Android Whiteboard | INF6502WB series INF6505 | 1 | ✓ | With Android Whiteboard | |
| Internet Browser | With LightCast Key | - | INF6502WB and INF6505 series with LightCast Key | With LightCast Key | 1 | - | |
| Document Viewer* | ✓ | - | INF6502WB series INF6505 | 1 | Limited | - | |
| 4K Resolution | 1080p | 1080p | 1080p | ✓ | ✓ | ✓ | |
| Capacitive Touch | ✓ | Infrared | ✓ | 1 | Infrared | Infrared | |
| Anti-Glare | - | - | ✓ | 1 | ✓ | ✓ | |

*Document viewer supports the following file types: pdf, doc, docx, xls, xlsx, ppt, pptx, avi, mkv, mpg, mpeg, mov, mp4, 3gp, rm, rmvb, jpg, jpeg, bmp, and png

| | 40-inch | 57-inch | 65-inch | 70-inch | 75-inch | 85-inch |
|------------------------|---------|---------|---------|---------|---------|---------|
| Small Team Area | 1 | 1 | | | | |
| Huddle Spaces | 1 | ✓ | | | | |
| Offices | 1 | ✓ | ✓ | | | |
| Meeting Rooms | | ✓ | ✓ | ✓ | ✓ | |
| Large Meeting Rooms | | | 1 | 1 | 1 | 1 |
| Classrooms | | | ✓ | ✓ | ✓ | ✓ |
| Lecture Halls | | | | ✓ | ✓ | ✓ |



"I use my iPad to cast live camera feed of what students have created to the JTouch.

-Mrs. Joy, 5th Grade School Teacher

Accessories for JTouch Displays

Mobile Carts

- Move your JTouch around the room or around the building
- Integrated cable management with flexible covers to hide cables for a clean installation
- Smooth rolling casters for effortless positioning (2 locking casters)
- Height adjustment 4-6' (1.2-1.8 m)

Lift Case

Easily store, transport, and use a 40", 57", 65", or 70" flat screen display. Set up displays with only one or two people and be ready for use in less than 5 minutes.

- Full range of viewing heights
- Mounted multi-outlet surge protected power strip
- Shock-mounted lift mechanism
- Pivoting mount on 40" case enables portrait or landscape 40-inch display
- Integrated cable management system
- 2-piece clamshell locking lid
- Stable, yet portable with four heavy duty casters

LiteShow 4

Add the InFocus LiteShow 4 wireless presentation adapter to any base model display with a VGA or HDMI input to quickly and easily share data, audio, and HD video over a secure wireless connection

- Connect LiteShow 4 to your network to create a new, secure wireless access point
- On-board video decoding for fast, smooth playback
- Guests quickly connect with LiteShow USB drive
- Compatible with Windows 7, 8 & 10, Mac & iOS and Android mobile devices
- Connect and display multiple computers at the same time

LightCast Key

The LightCast Key unlocks your JTouch's wireless casting, web browsing, document viewing and annotation, and wired LAN connectivity. LightCast functionality is built into select interactive displays.

- Connect mobile devices and share content wirelessly
- Capture, save, and share notes on an interactive whiteboard
- · Access the internet with a built-in web browser
- View and present documents, videos, and photos









Bring Your Display to Life with 4K

Boost the impact of your content and make every meeting or presentation more engaging, informative, and memorable with 4K models from InFocus.

- More pixels mean more detail and depth for amazingly life-like images
- Enhanced color rendering
- Presenters benefit from crisp, clear images up close
- Audiences enjoy vibrant, detailed images, even from the back of a conference room



Specifications*

InFocus

| Display | INF4030 INF4030p | INF5701 INF5701p | INF6500e INF6500eAG | INF6505 INF6505e INF6505AG INF6505eAG | INF6502WB INF6502WBp INF6502WBAG INF6502WBAGp | INF7002e | INF7002WB INF7002WBAG | INF7530AG INF7530eAG 75" Diagonal | INF8501 |
|---|--|---|--|--|--|--|---|---|---|
| Size Resolution | 40" Diagonal | 57" Diagonal 65" Diagonal | | | | 70" Diagonal | | | 85" Diagonal |
| | | | FULL HD 1920 × 1080 4K 3840 | | | | 4K 384U | × 2160 | Yes and |
| Anti-Glare | N/A | | INF6500eAG | INF6505eAG INF6502WBAG | | INF7002WBAG | | Yes | Gorilla Glass |
| Wireless Collaboration | LightCast ready*** | LiteShow 4 ready | | | LightCa | ghtCast ready | | LightCast embedded | LiteShow 4 ready |
| Mounting Orientation | Portrait / Landscape | | Landscape | | | | | | 1 |
| Technology | LED Edge-Lit LCD | | | | rect WLED Backlight | 1 | - | | LED Edge-Lit LCD |
| Pixel Pitch | 0.45mm | 0.67mm | | Dmm | 0.744mm | | Omm | 0.429mm | 0.46mm |
| Response Time | 8.5ms | 9.5ms | - | ns | 6.5ms | 6ms | | 8ms | 6ms |
| Contrast Ratio | | 00:1 | 4,00 | | | 5,000:1 | | 1200:1 | 3,000:1 |
| Brightness Input Connections Output Connections | 300cd/m ² HDMI × 4, VGA, component, composite, 3.5mm line-in audio (mono), RCA stereo audio, RS232, USB-B for touchscreen control, USB-A × 2 on panel, USB-A × 2 on battom for embedded software RCA Stereo Audio (L/R), USB-B for Touchscreen Control | HDMI ×2, VGA, RS232, RCA Stereo Audio, 3.5mm Line- in Audio (mono) RCA Stereo Audio (L/R), 3.5mm Stereo Audio, USB-B for Touchscreen Control | HDMI x5, VGA, Component Video, USB x2 rear, USB x3 front (PC USB on front reserved for future use), 3.5mm line-in audio (mono), RCA Audio (L/R), RS-232 RCA Stereo Audio (L/R), 3.5mm Stereo Audio, USB-B & USB-A for Touchscreen Control | HDMI x4, USB x3 on front, USB x2 on rear RJ-45 Ethernet, VGA, 3.5mm line-in audio (mono), component video, composite video, RS232 | | 350cd/m ² DisplayPort 1.2, HDMI 2.0 x 2, HDMI 1.4, VGA, component, 3.5mm line-in audio (mono), RCA stereo, RS232, USB-A x 4 on panel, USB-A x 2 on bottom for embedded software), 3.5mm Stereo Audio, hscreen Control | | 450cd/m ² HDMI x 5, VGA, PC Audio In (stereo, VGA Audio source), composite video, 1/8" Microphone (Mono linked to OPS), RS232, USB 2.0 x 2, USB 3.0 x 2, OPS PC USB x 2, RCA Audio (L/R, link to Component and Composite Video, Media USB (Android) HDMI Out, USB-B x 4 for Touchscreen Bontrol, 3.5mm PC Audio, 3.5mm PC Audio, 3.5mm | 500cd/m ² DisplayPort 1.2, HDMI 2.0 × 2(Rear), HDMI 1.4, VGA, component, 3.5mm line-in audio (mono), RCA Stereo audio, RCA Stereo audio, S.3.0 Type-A x4 RCA Stereo Audio (L/R), 3.5mm Stereo Audio, USB-B for Touchscreen Control |
| Touch Technology | PCAP | IR | IR PCAP | | | | (L/R), RS-232 3.5mm Stereo Audio, USB-B for Touchscreen Control | | |
| Touch Points | 10 | 5 | | | | 10 | | | |
| Speakers | | | | | 10W × 2 | | | | |
| Mount | Vesa standard 200 × 200mm M8 screws | Vesa standard 400 × 400mm M8 screws | | | | | Vesa 400 × 600mm M8 screws | | |
| Accessories Included | VGA cable, USB A-B cable, Power cord, Tray, Stylus, and Quick Start Guide | Power cord, VGA cable, USB A-B cable, Remote, Quick Start Guide | VGA cable, USB A-A cable, USB A-B cable, Power cord, Stylus, Remote, Quick Start Guide | HDMI cable, USB A-B cable, Power cord, Remote, Stylus, Quick Start Guide | VGA cable, USB A-B cable, Power cord, Remote, Stylus, Quick Start Guide | | HDMI cable, USB cable, Power cord, Stylus, Remote, Stylus, Quick Start Guide | Power cord, VGA cable, USB cable, Remote, Stylus, Quick Start Guide | |
| Product Weight | 44lbs / 20kg | 124lbs / 56kg | 110.2 lbs / 50 kg | | 117.5lbs / 53.5kg | 108lbs / 49kg | | 139lbs / 63Kg | 223.8lbs / 101.5kg |
| Product Dimensions (H × W × D) | 21.8 × 38.3 × 4.5in / 533 × 974 × 113mm | 33.6 x 54.5 x 3.5 / 853 x 1384 x 89mm | 38.3 x 59.9 x 3.3in / 972 x 1521 x 83mm | | 32.3 × 59.9 × 3.3in / 895 × 1520.5 × 83.1mm | 37.9 x 64.1 x 4.2 in / 963.3 x 1629.8 x 106.6 mm | | 59.4 x 4.8 x 34.9in / 1510 x 122 x 886mm | 46.7 x 78.3 x 4.4 in / 1186 x 1988 x 112.1 mm |
| Shipping Weight | 56.4lbs / 25.6kg | 153lbs / 69kg | 136.7lbs | s / 62 kg | 148.4lbs / 67.3kg | 136.7lb | s / 62 kg | 177lbs / 80kg | 264.6lbs / 120kg |
| Shipping Dimensions (H × W × D) | 28.1 × 41.9 × 7.9in / 715 × 1063 × 200mm | 42.5 × 63.5 × 10in / 1080 × 1613 × 254mm | 44.9 x 66.4 x 8.4in / 1141 x 1687 x 213mm | | 44 x 69 x 10.6in / 1128 x 1752 x 270mm | 46.5 x 73.2 x 10.2in / 1180 x 1860 x 260mm | | 69.5 x 12.6 x 45.9in / 1765 x 320 x 1165mm | 56.2 x 88.1 x 12.2 in / 1427 x 2239 x 311 mm |
| Warranty | | | | | 2 Years | | | | |

*Product specifications, terms, and offerings are subject to change at any time without notice. **Check with your manufacturer for details

***Wireless casting features of LightCast enabled when LightCast Key is inserted into any USB port.

Additional Display Specifications

Refresh Rate: 120 Hz Viewing Angle: 176° Computer Touch Compatibility (via USB): PC, Mac, Chromebook Power: AC 100 to 240V, 50/60 Hz Operating Conditions: 32° to 104° F at 0 to 10K feet / 0° to 40° at 0 to 3,048 m Noise: <40dBA at 77 F / 25 C

Accessories

Wall Mount for 57-75 Inch Display (INF-WALLMNT2) Mobile Carts for 57-75 Inch Display (INF-MOBCART, INF-MOBCARTPRO-B, INF-MOBCARTPRO-S) Wall Mount for 85-Inch Display (INF-WALLMNT3) Mobile Cart for 85-Inch Display (INF-MCART-PL) Deluxe Mobile Cart with PTZ Mount and Accessory Shelf (INA-MCARTDX) Lift Assist Mount for 57-75 Inch Display (INA-MNTBB70) Floor Support for Lift Assist Wall Mount (INA-SUPPORTBB) Mobile Cart for List Assist Mount (INA-CARTBB) VESA Interface Bracket for Lift Assist Mount (INA-VESABB) Floor Stand for 40-Inch DigiEasel (INA-STNDSM) LiteShow 4 (INLITESHOW4) LightCast Key (INA-LCKEY2, INA-LCKEY3 - selection is location dependent) Touchscreen Stylus (INA-STYLUS) Android Whiteboard Module (INA-AWB) BigNote Whiteboard Software (INS-BIGNOTE)

Extended Warranties: 40-Inch (EPW-40JT1, EPW-40JT2, EPW-40JT3) / 57-Inch (EPW-57JT1, EPW-57JT2, EPW-57JT3) / 65-Inch (EPW-65JT1, EPW-65JT2, EPW-65JT3, EPW-65SV1, EPW-65SV2, EPW-65SV3) / 70-Inch (EPW-70JT1, EPW-70JT2, EPW-70JT3) / 75-Inch (EPW-75JT1, EPW-75JT2, EPW-75JT3) / 85-Inch (EPW-85JT1, EPW-85JT2, EPW-85JT3)

