JTouch Interactive Display

Capacitive Touchscreen For K-12 Classrooms

Part #s: INF6500e, INF6500eAG



Designed specifically for the unique needs of the K-12 classroom, the 65-inch InFocus JTouch interactive display, featuring cutting-edge touch technology, engages the entire class at a price that fits your school's budget. Simply connect your PC, Mac or Chromebook to create a bright, colorful, and interactive touch experience.

Key Features

- Big, bright display at an affordable price that's right for your school's budget
- 1080p resolution for crisp, vivid images that can be seen from anywhere in the classroom
- Display your notebook via HDMI or VGA & control it from the display via touch using a USB cable
- Run all your Windows, Mac or Chromebook apps, even older ones, with touch
- 10 point touchscreen for more real-time editing
- Sleek, bezel-less design
- No calibration or special stylus needed means it's quick and easy to use with just your fingertips
- Front-facing, 20-watt speakers for robust sound
- Optional anti-glare available with JTouch INF6500eAG model



- HDMI to quickly connect your notebook
- USB port for optional on-board PC
- Two-port USB hub syncs with your connected notebook
- USB to enable notebook touch control



Projected Capacitive Touch

The same ultra-responsive capacitive touch technology found in smartphones and tablets is available in the INF6500e, with more touch points for fingers.



Specifications*

Size 65" Diagonal Resolution 1080p HD (1920 x 1080) Mounting Orientation Landscape Display Technology Direct LED backlight Pixel Pitch 0.40mm Response Time 8ms Contrast Ratio 4,000:1 Brightness 300cd/m2 Input Connections HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232 Output Connections RCA stereo audio out, 3.5mm stereo out Touch Technology Projected Capacitive Touch Points 10
Mounting OrientationLandscapeDisplay TechnologyDirect LED backlightPixel Pitch0.40mmResponse Time8msContrast Ratio4,000:1Brightness300cd/m2Input ConnectionsHDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232Output ConnectionsRCA stereo audio out, 3.5mm stereo outTouch TechnologyProjected Capacitive
Display Technology Direct LED backlight O.40mm Response Time 8ms Contrast Ratio 4,000:1 Brightness 300cd/m2 Input Connections HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232 Output Connections RCA stereo audio out, 3.5mm stereo out Touch Technology Projected Capacitive
Pixel Pitch Response Time 8ms Contrast Ratio 4,000:1 Brightness 300cd/m2 Input Connections HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232 Output Connections RCA stereo audio out, 3.5mm stereo out Touch Technology Projected Capacitive
Response Time Contrast Ratio 4,000:1 Brightness 300cd/m2 Input Connections HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232 Output Connections RCA stereo audio out, 3.5mm stereo out Touch Technology Projected Capacitive
Contrast Ratio 4,000:1 Brightness 300cd/m2 Input Connections HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232 Output Connections RCA stereo audio out, 3.5mm stereo out Touch Technology Projected Capacitive
Brightness 300cd/m2 Input Connections HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232 Output Connections RCA stereo audio out, 3.5mm stereo out Touch Technology Projected Capacitive
Input Connections HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232 Output Connections RCA stereo audio out, 3.5mm stereo out Touch Technology Projected Capacitive
component, composite, RS232 Output Connections RCA stereo audio out, 3.5mm stereo out Touch Technology Projected Capacitive
Touch Technology Projected Capacitive
Touch Points 10
Todal Folia
Speakers Front-facing 10W x 2
Mount Vesa standard 400 × 400mm M6 screws
Accessories Included VGA cable, USB cable, power cord, remote control, quick setup guide
Product Weight 110.2 lbs / 50 kg
Shipping Weight 136.7lbs / 62 kg
Product Dimensions (H x W x D) 38.3 x 59.9 x 3.3in / 972 x 1521 x 83mm
Shipping Dimensions (H x W x D) 44.9 x 66.4 x 8.4 / 1141 x 1687 x 213mm
Warranty 2 years

^{*} Product specifications subject to change without notice

Accessories

LiteShow 4 Wireless Display Adapter (INLITESHOW4)
Android Whiteboard Module (INA-AWB)
Wall Mount for 57-70 Inch Display (INF-WALLMNT2)
Mobile Carts for 57-70 Inch Display (INF-MOBCART, INF-MOBCARTPRO-B, INF-MOBCARTPRO-S)
Lift Assist Mount for 57-70 Inch Display (INA-MNTBB70)
Floor Support for Lift Assist Wall Mount (INA-SUPPORTBB)
Mobile Cart for List Assist Mount (INA-CARTBB)
VESA Interface Bracket for Lift Assist Mount (INA-VESABB)
Touchscreen Stylus (INA-STYLUS)
Extended Warranties (EPWHW65JT1, EPWHW65JT2, EPWHW65JT3)

Easily Upgrade to Whiteboard Functionality with Android Whiteboard:

Add the Android Whiteboard (INA-AWB) and your JTouch becomes a digital whiteboard that you can tailor to your class-room's needs — including access to nearly endless applications in the Google Play store.

- Save notes electronically
- Create a multi-screen canvas, with room for free-form drawings, diagrams, and notes
- en for ss, s
- Use it with fingers or a stylus
- Write or draw with complete collection of digital pens, highlighters, shapes, lines and colors
- · Paste images