

IN1156

Ultra-Portable LED Projector

Part #: IN1156

InFocus

The IN1156 ultra-portable projector is built to perform, with HDMI input, high brightness, ultra-long-lasting images, and unbeatable quality and color. Featuring a compact, light-weight design, the IN1156 is perfect for business travelers, or anyone who needs to take their presentation on the road.

Key Features

- ◆ Quantum Color Engine for vivid, ultra-long-lasting images
- ◆ Amazing 30,000-hour light source
- ◆ Green, mercury-free technology
- ◆ 3000 lumens
- ◆ Wireless, PC-less on-board document viewer with QuadView (with wireless adapter)
- ◆ Support for AirPlay and MiraCast



Quantum Color Engine

The IN1156 is powered by the InFocus Quantum Color Engine for exceptional image quality over years of continuous operation. The Quantum Color Engine is based on solid-state illumination technology, and is tested for over 200 unique color parameters to ensure the most vivid images possible. A massive color gamut, up to 40% bigger than leading competitors, and high color luminosity ratio bring your screen to life. With no color decay, you can enjoy remarkable images for over 3 years of 24/7 operation or over 10 years of business hour operation.

Superior Images

Get quality images and true-to-life colors with DLP technology with InFocus BrilliantColor implementation. 3,000 lumens mean bright, clear images even with the lights on, and 1,000,000:1 contrast ratio adds sharpness with darker blacks and whiter whites.

Greener Technology, Greater ROI

Solid-state technology means your projector will last an amazing 30,000 hours, with an environmentally friendly mercury-free design. No lamps to replace means less hassle and fewer added expenses over time

Specifications*

Projector
Resolution – Native

IN1156
WXGA (1280 x 800)

Projector	IN1156
Display Technology	DLP with LED light source
Video Standard Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Speakers	Mono 3W x 1
Lamp Brightness	3,000 lumens
Lamp Life	30,000 hours
Lamp Power	106W
Contrast Ratio	1,000,000:1
Number of Colors	1.08 billion
Synch Scan Frequency – Horizontal	15 ~ 102 KHz
Synch Scan Frequency – Vertical	24 ~ 120 KHz
Aspect Ratio	16:10
Aspect Ratio Compatibility	4:3, 16:9, 2.35:1, 1:1, 2:1, 13:9, 15:9, 5:4
Projection Lens F-Stop – Minimum	1.70
Image Size – Minimum	30 in
Image Size – Maximum	300 in
Projection Offset	103%
Keystone Correction	± 40°
Connectors – Inputs	3.5mm audio, Composite video, USB A x2, HDMI, VGA
Connectors – Outputs	3.5mm audio output
Audible Noise	< 33 dBA at 0°F / -17.8°C
Audible Noise – Eco Mode	< 26 dBA at 0°F / -17.8°C
Included Accessories	Power cord, Remote, HDMI Cable, Documentation, Quick Start Guide, Carrying case, User Manual (CD), Lens cap
3D Support	720p @ 120Hz, DLP Link 3D glasses required, SVGA, XGA
Product Warranty	2 years
Video Player Compatibility	AVI, MKV, MP4, MPEG-1 (MPG, MPEG), WMV, MOV
Photo Viewer Compatibility	JPEG and JPG, Bitmap (BMP)
Music Player Compatibility	MP3, WMA, AAC, WAV
Power Consumption	215.0W max
Power Consumption – Standby Mode	0.5W max
Power Standard	AC 100 to 240V, 50/60
Documentation Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Arabic, Indonesian, Portuguese
Menu Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Polish, Turkish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai
Operating Pitch/Roll	360 degree operation
Illumination Technology	LED, InFocus Quantum Color Engine
Display Technology	DLP .45" S310
Uniformity	JBMA 85% ANSI 70%
Zoom Ratio	Fixed
Throw and Zoom	
Throw Distance – Minimum	0.8 m
Throw Distance – Maximum	8.0 m
Throw Ratio	1.20:1
Shipping	
Product Dimensions	2.2 x 11.7 x 7.9 in / 55.9 x 297.2 x 199.9 mm
Product Weight	4.4 lbs / 2 kg

* Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

Universal Projector Ceiling Mount (PRJ-MNT-UNIV)
 InFocus Standard Replacement Remote (HW-NAVIGATOR-5)
 SimpleShare Presentation System (INA-SIMPS1)
 LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)
 LiteShow Mount Adapter (PRJ-MNT-LS3)
 SimpleShare Touch Presentation System (INA-SIMINT1)

SimpleShare (INA-SIMS1)

DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)

Soft Projector Carry Case (CA-SOFTCASE-VAL3)

Fixed Frame Projector Screen: 94 in., 16:10 (SC-FFW-94)

Fixed Frame Projector Screen: 130 in., 16:10 (SC-FFW-130)

Motorized Electric Projector Screen: 94 in., 16:10 (SC-MOTW-94)

Motorized Electric Projector Screen: 113 in., 16:10 (SC-MOTW-113)

Motorized Electric Projector Screen: 130 in., 16:10 (SC-MOTW-130)

Manual Pull Down Projector Screen: 94 in., 16:10 (SC-PDW-94)

Manual Pull Down Projector Screen: 109 in., 16:10 (SC-PDW-109)

1 Year Extended Warranty for IN1XXX, IN2XXX, IN3XXX Projectors (EPW-PJM1)

2 Year Extended Warranty for IN1XXX, IN2XXX, IN3XXX Projectors (EPW-PJM2)