

INA-PTZ-4

InFocus

Give everyone the best view in the room

Part #: INA-PTZ-4

The InFocus RealCam pan/tilt/zoom professional-quality 1080p HD camera bundle makes video conferencing meetings shine.

Key Features

- ◆ Full 1080p HD resolution
- ◆ Pan, tilt and zoom using the included remote control
- ◆ 72.5-degree wide-angle lens
- ◆ USB 3.0 ultra-high speed interface
- ◆ 12x optical zoom and 32x digital zoom
- ◆ Use any PC with any software or OS via USB
- ◆ Pan angle of -170° to $+170^{\circ}$
- ◆ Tilt angle of -30° to $+30^{\circ}$
- ◆ Power adapter required (not supplied) outside North America



Broad Range, Flexible Control, Vivid Images

Quiet pan/tilt action is ideal for capturing extensive areas. Access the precise settings you use most with 255 position presets for pan, tilt, and zoom, focus position, exposure mode, and white balance mode. Features a full function USB interface, with USB 3.0 and USB 2.0 compatibility, support audio and support UVC protocol. Control it with RS232 or USB UVC compatibility.

Use any Computer Conferencing App

RealCam makes applications like ConX Cloud from InFocus, as well as Skype, Skype for Business, and GoToMeeting, come alive with realistic full HD wide-angle video quality. Plug RealCam directly into a Mondopad or other PC with USB 3.0, without a separate capture device.

Compatible with Major Video Platforms

RealCam works with nearly all major platforms for video at up to 1080p (if allowed by that service). Use with Microsoft Skype for Business, Adobe Connect, Citrix GoToMeeting, LifeSize ClearSea, Avistar C3, Cisco Jabber, Skype, Polycom Real Presence Desktop, Radvision Scopia Desktop, and Google

Hangout. RealCam also works with InFocus Mondopad and ConX Cloud software.

Pair it with an InFocus Thunder Speakerphone

Add a Thunder speakerphone for crystal clear sound and images during your video calls. Connect Thunder to a Mondopad via USB or to a notebook, tablet, or mobile phone via Bluetooth. It also works great with PC-based communication software.



Specifications*

| RealCam PTZ Camera | |
|----------------------------------|--|
| Input Voltage | DC 12V |
| Product Dimensions | 5 x 4.6 x 6.1 in / 127 x 116.8 x 154.9 mm |
| Product Warranty | 1 year |
| Product Weight | 2 lbs / 0.9 kg |
| Shipping Dimensions | 10.2 x 9.8 x 9.8 in / 259.1 x 248.9 x 248.9 mm |
| Shipping Weight | 4.4 lbs / 2 kg |
| Accessories Included | Power cord, USB cable, serial cable, remote |
| Audio Input | 1-ch: 3.5mm Audio Interface, Line In |
| Backlight Compensation | Supported |
| Color System | YUV 4:2:2 / H.264 / MJPEG |
| Compatible Video Platforms | (up to 1080p if allowed by service) Skype for Business, Adobe Connect, Citrix GoToMeeting, LifeSize ClearSea, Avistar C3, Cisco Jabber, Skype, Polycom Real Presence Desktop, Radvision Scopia Desktop, Google Hangout, InFocus Mondopad, ConX Cloud |
| Control Input/Output | 1xRS-232 IN: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D/Pelco-P 1xRS-232 OUT: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA network use only |
| Current Consumption | 1.0A (Max) |
| Digital Noise Reduction | 2D&3D Digital Noise Reduction |
| H & V Flip | Supported |
| Horizontal Angle of View | 72.5° to 6.9° |
| Horizontal Rotation Range (Pan) | ±170° (max. speed 100°/sec.) |
| Image Freeze | Supported |
| Input Voltage | DC 12V |
| Lens | 12x, f3.5mm ~ 42.3mm, F1.8 ~ F2.8 |
| Minimal Illumination | 0.05 Lux @ (F1.8, AGC ON) |
| Operating System | Windows 7, Windows 8, Windows 10, Mac OS X |
| Operating Temperature F(C) | -10°C ~ 40°C |
| Power Connector | JEITA type (DC IN 12V) |
| Power consumption | 12 W (Max) |
| Preset Accuracy | 0.1° |
| Presets (number) | 255 |
| Regulatory Mariks | Camera: FCC, CE, IC / Power Supply: CB, UL, CCC |
| Scanning Mode | Progressive |
| Sensor | 1/2.7", CMOS, Effective Pixel: 2.07M |
| Shutter | 1/30s ~ 1/10000s |
| Storage Temperature | -40°C ~ 60°C |
| USB | 1xUSB3.0: Type B female jack |
| USB Video Communication Protocol | UVC 1.0 ~ UVC 1.5 |

RealCam PTZ Camera

| | |
|--------------------------------|---|
| UVC PTZ | Supported |
| Vertical Angle of View | 44.8° to 3.9° |
| Vertical Rotation Range (Tilt) | ±30° (max. speed 69.9°/sec.) |
| Video Format | USB3.0 : 1080p/60, 1080p/50, 1080p/30, 1080p/25, 720p/60, 720p/50, 720p/30, 720p/25 USB2.0 : 1080p/30, 1080p/25, 1080p/15, 1080p/10, 720p/30, 720p/25, 960x540p/30, 960x540p/25, 640x360p/60, 640x360p/50 |
| Video S/N | >/= 55dB |
| Video System | HD: 1080p/60, 1080p/50, 1080p/30, 1080p/25, 720p/60,720p/50, 720p/30, 720p/25 |
| White Balance | Auto, Indoor, Outdoor, One Push, Manual |
| Zoom | 12x optical, 32x digital |

* Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

- Webcam Shelf for Pro Mobile Cart or Wall Mount (INF-VIDSHELF2)
- PTZ Camera Shelf (Upper) for Mondopad or BigTouch (INF-PTZMNTU)
- Webcam Shelf for Mobile Cart or Floor Stand (INF-VIDSHELF)