



205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com



Large touchscreen displays to engage your audience and fit your budget

The InFocus JTouch combines precise 5-point touchscreen technology with a bright, colourful LCD display to engage audiences in classrooms and beyond.

- 55-inch or 70-inch 1080p touch display for a great price
- O Run all your Windows apps, even the older ones, in touch mode
- O Your content will be interactive, bright and crisp in any light
- Accurate and responsive touch overlay with 5-point touch capability
- Easy to connect to your PC via USB



Specifications*

Display	INF5520A-NOPC	INF7001
Size	55" diagonal	70" diagonal
Resolution	1920 × 1080	
Refresh Rate	60 Hz	120 Hz
Viewing Angle	±89°	±88°
Technology	CCFL LCD	a-Si TFT active matrix LCD
Pixel Pitch	0.63mm	
Picture-in-Picture	SBS/4 quadrant PiP	N/A
Video Input Compatibility	Full NTSC, 480i, 480p, 720p, 1080i, 1080p/24, 1080p/30, 1080p/60	
Data Input Compatibility	$VGA (640 \times 480), SVGA (800 \times 600), XGA (1024 \times 768), SXGA (1280 \times 1024), SXGA + (1400 \times 1050), UXGA (1600 \times 1200), WXGA + (1440 \times 900), WSXGA + (1680 \times 1050), WXGA (1280 \times 800), WUXGA (1920 \times 1200), WSXGA + (1680 \times 1050), WSXGA$	
Input Connections	HDMI × 2, VGA (HD15 VESA), Component, S-Video, Composite, RS232,	HDMI x 2, VGA (HD15 VESA), 3.5mm stereo mini-jack, RCA stereo audio in,
	RCA stereo audio × 2, 3.5 mm stereo mini-jack,	3.5mm stereo audio in, USB Type-B to touch screen controller board
	USB Type-B to touch screen controller board	
Output Connections	RCA audio stereo (L/R) output	RCA audio stereo (L/R) output, 3.5mm stereo mini jack
Touch Screen	Edge-to-edge quad camera multi-touch system with support for 5 point Windows 7/8 gestures (not compatible with Mac OS).	
	Glass protection overlay for LCD surface. USB connection to PC from touch system panel board	
Speakers (Integrated)	Stereo 7W × 2	
Power	AC 100 to 240V, 50/60Hz	
Mount	VESA standard 400 × 400mm M6 screws	
System		
Accessories Included	cleaning cloth, VGA cable, USB cable, security screws with removal tool,	
	power cord, remote control, quick setup guide, feet/table stand assembly (feet not included with INF7011)	
Warranty	1 Year	
Product Weight	55.5 kg	70.3 kg
Product Dimensions	1346 x 140 x 820 mm	1589 × 60 x 927 mm
Shipping Weight	61.2 kg	77.6 kg
Shipping Dimensions	1490 x 352 x 975 mm	1854 x 267 x 1245 mm
Operating Conditions	5 to 35°C at 0 to 3,048 m	
Noise	<40dBA @ 25°C	
Energy Star	5.1 for display and PC	

 $[\]mbox{\ensuremath{^{\star}}}$ Product specifications, terms, and offerings are subject to change at any time without notice.

