

C360 Tip Range for DS360 Micro Desoldering Iron











Ref.	Description	Image and dimensions	Suggested components	Compatible with
C360012	Micro Desoldering Tip Ø 0.8 mm Pad Ø 0.032 in		Pad desoldering	Stations: CDD, DIU, DDU, DMU Tool: DS360 Modules: MSE, MS
C360013	Micro Desoldering Tip Ø 1 mm Pad Ø 0.039 in		Pad desoldering	Stations: CDD, DIU, DDU, DMU Tool: DS360 Modules: MSE, MS
C360014	Micro Desoldering Tip Ø 1.2 mm Pad Ø 0.047 in		Pad desoldering	Stations: CDD, DIU, DDU, DMU Tool: DS360 Modules: MSE, MS

C560 Tip Range
for DR560 Desoldering Iron











Ref.	Description	Image and dimensions	Suggested components	Compatible with
C560001	Desoldering Tip Ø 0.6 mm HT Ø 0.024 in		Through-hole Desoldering	Stations: DIU, DDU, DMU Tool: DR560 Modules: MSE, MS
C560014	Desoldering Tip Ø 0.8 mm Ø 0.032 in		Through-hole Desoldering	Stations: DIU, DDU, DMU Tool: DR560 Modules: MSE, MS
C560002	Desoldering Tip Ø 0.8 mm HT Ø 0.032 in		Through-hole Desoldering	Stations: DIU, DDU, DMU Tool: DR560 Modules: MSE, MS
C560003	Desoldering Tip Ø 1 mm Ø 0.039 in		Through-hole Desoldering	Stations: DIU, DDU, DMU Tool: DR560 Modules: MSE, MS
C560017	Desoldering Tip Ø 1.1 mm Ø 0.043 in		Through-hole Desoldering	Stations: DIU, DDU, DMU Tool: DR560 Modules: MSE, MS
C560004	Desoldering Tip Ø 1.3 x Ø 3.2 mm Ø 0.052 x Ø 0.126 in		Through-hole Desoldering	Stations: DIU, DDU, DMU Tool: DR560 Modules: MSE, MS
C560009	Desoldering Tip Ø 1.3 x Ø 5 mm Ø 0.052 x Ø 0.197 in		Through-hole Desoldering	Stations: DIU, DDU, DMU Tool: DR560 Modules: MSE, MS

C560 Tip Range for DR560 Desoldering Iron

	Ref.	Description	Image and dimensions	Suggested components	Compatible with
	C560005	Desoldering Tip Ø 1.5 mm Ø 0.059 in		Through-hole Desoldering	Stations: DIU, DDU, DMU Tool: DR560 Modules: MSE, MS
	C560006	Desoldering Tip Ø 1.9 mm Ø 0.075 in		Through-hole Desoldering	Stations: DIU, DDU, DMU Tool: DR560 Modules: MSE, MS
	C560018	Desoldering Tip Ø 2.2 mm Ø 0.087 in		Through-hole Desoldering	Stations: DIU, DDU, DMU Tool: DR560 Modules: MSE, MS
	C560007	Desoldering Tip Ø 2.4 mm Ø 0.095 in		Through-hole Desoldering	Stations: DIU, DDU, DMU Tool: DR560 Modules: MSE, MS
	C560015	Desoldering Tip Ø 3 mm Ø 0.118 in		Through-hole Desoldering	Stations: DIU, DDU, DMU Tool: DR560 Modules: MSE, MS
		C560011	Desoldering Tip Ø 0.6 mm HT Pad Ø 0.024 in		Pad desoldering
C560012		Desoldering Tip Ø 0.8 mm HT Pad Ø 0.032 in		Pad desoldering	Stations: DIU, DDU, DMU Tool: DR560 Modules: MSE, MS
C560013		Desoldering Tip Ø 1 mm Pad Ø 0.039 in		Pad desoldering	Stations: DIU, DDU, DMU Tool: DR560 Modules: MSE, MS

W140 Blade Cartridge Range
for **WS140** High-Temperature Precision
Wire Stripper Tweezers



	Ref.	Description	Image and dimensions	Suggested components	Compatible with
	W14014G	Single-Hole Cartridges Solid Wire 14 AWG		Wire insulation stripping	Station: WSS Tool: WS140
	W14016G	Single-Hole Cartridges Solid Wire 16 AWG		Wire insulation stripping	Station: WSS Tool: WS140
	W14018G	Single-Hole Cartridges Solid Wire 18 AWG		Wire insulation stripping	Station: WSS Tool: WS140
	W14020G	Single-Hole Cartridges Solid Wire 20 AWG		Wire insulation stripping	Station: WSS Tool: WS140
	W14022G	Single-Hole Cartridges Solid Wire 22 AWG		Wire insulation stripping	Station: WSS Tool: WS140
	W14024G	Single-Hole Cartridges Solid Wire 24 AWG		Wire insulation stripping	Station: WSS Tool: WS140
	W14026G	Single-Hole Cartridges Solid Wire 26 AWG		Wire insulation stripping	Station: WSS Tool: WS140
	W14028G	Single-Hole Cartridges Solid Wire 28 AWG		Wire insulation stripping	Station: WSS Tool: WS140