

SMD Rework System

SRWS-S

SRWS rework system provides full control over SMD components rework processes.

The Hot Air Station JTSE controls the rework task using temperature and air flow profiles.

The Rework Arm RWS supports the Hot Air Heater allowing handsfree operation.

The Pre Heater Set PHS-KB comes with an Infrared Heater and a PCB Support.

A variety of Protectors, Extractors and Tripods are included.

100V Ref. SRWS-9SA

120V Ref. SRWS-1SA

230V Ref. SRWS-2SA



Specifications

Common Data:

Voltage	according to model: 120V / 230V / 100V
ESD safe	
Package weight	0,000 kg (0.00lb)
Package dimensions	183 x 60 x 34 mm (7.20 x 2.36 x 1.34 in)

JTSE Data: [click here](#)

PHS Data: [click here](#)

RWS Data: [click here](#)

Connectables

Accessories

Pedal
P-005



Connectables

Consumables

Thermocouple Type K
PH218



Kapton tape
PH217



Thermally Conductive Tape 25
mm
PH223



Thermally Conductive Tape 50
mm
PH222



Documentation

Manuals

JTSE-A Manual
IR Preheater Set Manual
RWS-B Manual

Exploded View

JTSE-A Exploded View
PHS-KB Exploded View from series 163972
RWS-B Exploded View